



ELIKA PRO

Active helical UHF band aerial complete with F connector and an LED monitoring system and an automatic gain control (AGC).

- It is an evolution of the Loop Yagi technology, already adopted to Fracarro.
- No tool needs for mounting ELIKA series, thanks to premounted elements, quick coupling radiator and reflectors and mast bracket with zenith adjustment and large wingnut.
- **4G LTE filter** inserted in the radiator dipole.
- High gain, extraordinary directivity and almost total absence of the lateral lobes.
- Exclusive Elika design patented by Fracarro.
- Single packaging with plastic bag.

CODE		213227
Elements	no.	1
Band		UHF
Channels		E21-E60
Bandwidth	MHz	470-790
Gain	dBi	47,5
AGC Dynamic	dΒμV	65-80
Output level	dΒμV	98
Power supply	V	12-24
Current consumption	mA	45
Front/Back ratio	dB	32
Return loss	dB	-15

Data sheet



Beamwidth (-3dB)	0	±18
Wind load at 120km/h (720N/m²)	kg (N) 19 (186.2)
Connector	Type	F
Impedance	Ω	75
Max mast (Ø)	mm	60
Dimensions (L x H x W)	cm	92 x 82 x 62
Quantity Masterbox	pcs	10 (Single with plastic bag)
Unit weight	kg	2.30
Total weight	kg	27.6
Accessories		
Horizontal polarization		Included
Horizontal polarization Tilt adjustment		Included
Vertical polarization		Included
Vertical polarization Tilt adjustment		Included
Auxiliary boom		N.P.



