



SCHEMATIC		
MODEL NO	C	

NO.	Description	Material	Q'TY	Finish
6.	Cover	PBT+30% Fibre Glass	1	Black Color
5.	Housing	PBT+30% Fibre Glass	1	Black Color
4.	Pin(2.0φ)	Copper	1	Nickel Plated
3.	Break Terminal	0.4T Brass	1	Silver Plated
2.	Sleeve Spring	0.2T Phosphor Bronze	1	Silver Plated
1.	Pin Terminal	0.4T Brass	1	Silver Plated

S.C. PRECISION INDUSTRIAL CO., LTD.

PART NAME : DC POWER JACK PART NUMBER: SCD438CCS011B00G

TOLERANCE : $\pm 0.3\text{mm}$ UNLESS OTHERWISE SPECIFIED

DATE	DWN	CHKD	APVD	MANAGER
12.08.2005	易愛娣			總經理 黃振文
VERSION: 4.0				SCALE: 1/1

SPECIFICATIONS:
 Contact Resistance : $30\text{m}\Omega$ max
 Insulation Resistance : $100\text{M}\Omega$ min. at DC 500V
 Dielectric Withstand Voltage : AC 500V for one minute
 Remark: ▲: The Most Important Dimension

旭全
精密工業(深圳)有限公司
2005.12.24.
圖面發行

文管
中心發行
2005.12.24.
趙