


PCB LAYOUT  
(Top View)



**SPECIFICATION :**

**1. Electrical Char.**

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20M-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC
- Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

**2. Physical char.**

- Housing : PBT Glass Filled (UL 94V-0)
- Color : Black Color
- Spring Wire : 0.45mm Dia. Phosphor Bronze  
Gold Plating Over Nickel
- Temperature Range : - 25 /+90 Deg C
- Durability : 500 Mating cycles Min.

**AJ-026-6-X-X**

B=6p2c , C=6p4c  
D=6p6c

Gold plated 1=15u , 3=50u  
2=30u , 4= 6 u

**ALLEN CREATIONS CORP.**  
**端訊企業有限公司**

TITLE

RJ11 or RJ12 Mini Low Profile PCB Jack  
UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR  
AJ-026-6-X-X

SCALE SIZE DWG. NO. 9612 SERIES

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR.	DATE
 THIRD ANGLE PROJECTION	LINEAR $\frac{MM}{INCH}$	00±0.01	00±0.25	CK'D	SEP-09 '04
		000±0.005	000±0.13	Johnn	SEP-09 '04
	ANGLE+0'30'	RADIL	+0.45 -0.15	APP'D Billy	SEP-09 '04

DWG. NO.  
**AS026003**