

#### **Tube Rollers**

Tube Rollers are used for uniform mixing of blood samples, viscous liquids, and whole blood components in the anticoagulation tubes or bottles. These rollers can mix samples in any type of liquid containers. Tube rollers are controlled by microprocessor with digital timer.

## MX-T6-Pro

**Tube Roller** 

#### **Features**

- Maximum load of up to 4Kg.
- Gentle mixing in rolling motion with a capacity of 6 tubes.
- LCD digital display of adjustable speed and time.
- Speed adjustable from 10-70rpm and timer from 1-1199min.
- LED overload indicator.



### MX-T6-S

**Tube Roller** 

#### **Features**

- Maximum load of up to 4Kg.
- Gentle mixing in rolling motion with a maximum of 6 tubes capacity.
- Speed adjustable from 0-70rpm.
- LED power indicator.



#### **Specifications**

| Amplitude                                          |
|----------------------------------------------------|
| Motor type                                         |
| Rocking motion                                     |
| Max. load capacity                                 |
| Number of rollers                                  |
| Roller size[length]                                |
| Speed range                                        |
| Speed display                                      |
| Timer                                              |
| Timer display                                      |
| Time setting range                                 |
| Operation mode                                     |
| Voltage                                            |
| Power                                              |
| Dimension [D×W×H]                                  |
| Weight                                             |
| Permissible ambient<br>temperature and<br>humidity |
| Protection class                                   |

# MX-T6-Pro 24mm

DC motor
Rocking and rolling
4kg
6
280mm
10 -70rpm
LCD
Yes
LCD
1-1199min
Continuous/timer
100-240V,50/60Hz
30W
450×260×120mm
5.1kg

5-40°C.80%RH

IP21

## MX-T6-S

| 24mm                |
|---------------------|
| DC motor            |
| Rocking and rolling |
| 4kg                 |
| 6                   |
| 280mm               |
| 0-70rpm             |
| Dial                |
| -                   |
| -                   |
| -                   |
| Continuous          |
| 100-240V,50/60Hz    |
| 25W                 |
| 450×260×120mm       |
| 4.5kg               |
| 5-40°C,80%RH        |
| IP21                |

