

OIL-TEST CENTRIFUGE

4 x 100 ml

OLEUM

The OLEUM centrifuge is a compact tabletop device that is used for petroleum testing. During this process, the water content in the mineral oil is examined. The OLEUM features a 4-place swing-out rotor that can accommodate conical and pear-shaped ASTM tubes.



Information about the control panel can be found on page 8.

TECHNICAL SPECIFICATIONS

MAX. SPEED	3,000 rpm
MAX. RCF	2,213 xg
MAX. VOLUME	4 x 100 ml
SPEED RANGE	200 – 3,000 rpm
RUNNING TIME	59 min 50 s / 10 s increments or 99 h 59 min / 1 min increments
DIMENSIONS (W X H X D)	22 in x 16 in x 25 in / 56 cm x 41 cm x 64 cm
WEIGHT	159 lbs / 72 kg

ORDER NUMBERS

Z600-OL, 230 V / 50 – 60 Hz / 950 W

SPECIFICATIONS

- Maintenance-free induction motor
- Microprocessor control with LCD display
- Motor driven lid lock
- Active imbalance detection and shutdown
- Noise level < 55 dBA at max. speed
- Acoustic signal at the end of the running time
- Manufactured in accordance with international safety guidelines, e.g. IEC 61010
- Stainless steel chamber
- Timer function: the centrifuge starts at the pre-set time

ROTORS

Order number: Z600-OL-COM



Swing-out rotor 4 x 100 ml

Angle: 0 – 90°

MAX. SPEED:	3,000 rpm
Max. RCF:	2,213 xg
Max. Radius:	22 cm