

96-CHANNEL DISPENSER FOR FILLING OF MICROPLATES

- ◆ Intended for high throughput applications
- ◆ Each well of the standard 96-well microplate can be filled with different fluid
- ◆ Filling time for a microplate less than 1 second
- ◆ Automatic start of dispensing by inserting individual microplates
- ◆ Used e.g. for prefilling MIC microplates
- ◆ User-friendly operation, touch screen display, language selection, microplate counter
- ◆ Storage for up to 20 dispensing programmes
- ◆ Minimal losses of dispensed reagents
- ◆ Minimal operation and maintenance costs
- ◆ High dispensing precision and uniformity
- ◆ Automatic (programmable) purge & decontamination process

Made in
the Czech
Republic



TECHNICAL SPECIFICATIONS

Power supply: 230 V (850 VA)

Weight: 166 kg

Dimensions (W x D x H): 1 300 x 450 x 1 100 mm

Dispensing volume: 50 - 300 μ l (\pm 5 %)

Microplate dispensing time: < 0.6 sec

Dispensing uniformity: < 5% at 100 μ l

Vero2_10/2018



EUROPEAN UNION
European Regional Development Fund
OP Entrepise and Innovations
for Competitiveness

PRODUCER

DYNEX TECHNOLOGIES, spol. s r.o.
Place of business: Lidická 977, 273 43 Bustehrad, The Czech Republic
Headquarters: Vodickova 791/41, 110 00 Praha 1, The Czech Republic
tel.: + 420 220 303 600, fax: +420 224 320 133
email: export@dynex.cz
www.dynex.eu



DISTRIBUTOR

