

Thaitech Generator

The leader of Genset



Model : TTG-15P

Powered by PERKINS Diesel Engines



Technical Data

Standby	16.5 kVA / 13.2 kW
Prime	15 kVA / 12 kW
Rated Speed	1500 RPM
Output Frequency	50 Hz
Rated Voltage	400/230V
Phase	3
Power Factor	0.8
Ambient Temperature	< 50 C

Engine Data

Cycle	4 stroke
Combustion System	Indirect injection
Compression ratio	22.5:1
Cooling System	Water cooled
Total Coolant Capacity	6.0 litres
50% Fuel Consumption	2.24 l/hr
75% Fuel Consumption	3.11 l/hr
Prime power Fuel Consumption	5.0 l/hr
Standby Power Fuel Consumption	6.0 /hr
Engine Model:	403A-15G2
Number of cylinders	3 vertical in-line
Bore&Stroke	84x90 mm
Displacement	1.496 litres
Aspiration	Naturally aspired

Basic Configuration

- Starting battery
- Automatic mains failure control panel
- Generator Circuit Breaker
- Fuel tank

Alternator Data

Number of Phase	3
Connection Type	3 Phase 4 Wires "Y" type connecting
Number of Bearing	1
Protection Grade	IP23
Exciter Type	Self Excited / PMG
Insulation Class	H
Temperature Rise	H
Alternator Capacity	17 kVA
Alternator Efficiencies	0.872
Execution	Brushless

Dimensions and Weight

Genset Type	Open	Canopy
Length (mm)	1250	1650
Width (mm)	500	840
Height (mm)	1100	1450
Weight (kg)	370	770

photographs are for illustrative purposes only and may not reflect final specification.

This document is not contractual. According to our product improvement, we reserve the right to change specifications without notice.

Certified Company
ISO 9001
ISO 14001



THAITECH GENERATOR Co.,Ltd.
Office : 50/10 Metalian Tower3 Rama1 Rd., Pathumwan, Bangkok 10330 Tel. +662-612-3533 Fax. +662-612-3535 #409
Factory : 44/3 Moo 6 Tambon Klongkone, Amphermueang, Samutsongkharn province 75000 Tel. +663-475-6471
Email : thaitechgen@yahoo.com www.thaitechgen.com