

"CM" ลำโพงสำหรับติดตั้งบริเวณฝา/เพดาน และกำแพง

"CM" LOUNDSPEAKER WALL MOUNTING/CEILING MOUNTING



Loundspeaker

CM-0403A / CM-0405A / CM-0506A1

CM-0403B / CM-0405B / CM-0506B1

CM-0403D / CM-0405D / CM-0506D1

ISO9001 APPROVAL : CE



ลำโพงสำหรับติดตั้งติดผนัง

MODEL	CM-0403A	CM-0405A	CM-0506A1
	4 inch cone-type speaker		5 inch cone-type speaker
RATED INPUT	3W	5W	4W / 6W
RATED IMPEDANCE	100V , 3W (3.3KΩ)	100V , 5W (2KΩ)	100V , 4W (2.5KΩ) / 6W (1.7KΩ)
FREQUENCY RESPONSE	200Hz~12KHz		
SOUND LEVEL	Above 92dB (1m / 1w) L level		
MATERIAL / THICKNESS	ABS / 3mm thickness		
DIMENSION (MM)	190(H) x 192(W) x 95(D)		

ลำโพงสำหรับติดตั้งฝ้าเพดาน

MODEL	CM-0403B	CM-0405B	CM-0506B1
	4 inch cone-type speaker		5 inch cone-type speaker
RATED INPUT	3W	5W	4W / 6W
RATED IMPEDANCE	100V , 3W (3.3KΩ)	100V , 5W (2KΩ)	100V , 4W (2.5KΩ) / 6W (1.7KΩ)
FREQUENCY RESPONSE	200Hz~12KHz		
SOUND LEVEL	Above 92dB (1m / 1w) L level		
MATERIAL / THICKNESS	ABS / 3mm thickness		
DIMENSION (MM)	Φ200 × 60(D)mm		
MOUNTING HOLE (MM)	Φ175 mm		

ลำโพงสำหรับติดตั้ง ผนัง/ฝ้าเพดาน

MODEL	CM-0403D	CM-0405D	CM-0506D1
	4 inch cone-type speaker		5 inch cone-type speaker
RATED INPUT	3W	5W	4W / 6W
RATED IMPEDANCE	100V , 3W (3.3KΩ)	100V , 5W (2KΩ)	100V , 4W (2.5KΩ) / 6W (1.7KΩ)
FREQUENCY RESPONSE	200Hz~12KHz		
SOUND LEVEL	Above 92dB (1m / 1w) L level		
MATERIAL / THICKNESS	ABS / 2mm thickness		
DIMENSION (MM)	Φ182 × 66.5(D)mm		