

แบตเตอรี่ สำหรับไฟฉุกเฉิน ยี่ห้อ Sunny SN2.9-12 12Volt 2.9Ah
Seal lead acid recharge battery Sunny SN2.9-12 12Volt 2.9Ah



Specifications

Nominal Voltage(V) 12V

Nominal Capacity

20 hour rate	(0.145Ato10.50V)	2.9Ah
10 hour rate	(0.276Ato10.50V)	2.75 5Ah
5 hour rate	(0.493Ato10.20V)	2.46 5Ah
1 C	(2.9Ato9.60V)	1.64 3Ah
3 C	(8.7Ato9.60V)	1.16 Ah

Weight Approx.1.19Kg(2.62Lb s.)

Internal Resistance (at 1KHz) Approx. 33 mΩ

Maximum Discharge Current for

5 seconds: 4 3.5A

Charging Methods at 25°C (77 °F)

Cycle use:

Charging Voltage 14.4 to 15.0V
Coe cient -5.0mV/ C/c ell
Maximum Charging Current: 0.39A

Standby use:

Float Charging Voltage 13.5 to 13.8 V
Coe cient -3.0mV/ C/cell

Operating Temperature Range

Charge -15 C (5 F) to40 C (104 F)
Discharge -15 C (5 F) to50 C (122 F)
Storage -15 C (5 F) to40 C (104 F)

Charge Retention (shelf life) at 20°C(68°F)

1 month	92%
3 month	90%
6 month	80%

Case Material ABS UL94 H B

Option: Flammability resistance of (UL94 V-0)

Terminal F1 or F2 (Faston Tab 187 or 250)



Dimensions mm(inch)

