

A FIRE PLUS

จำหน่ายสินค้าประเภทงานดับเพลิงทุกชนิด

© COPYRIGHT ALL RIGHTS RESERVED. WWW.AFIRE.CO.TH

PRODUCT DATA SHEET | PRODUCT SPECIFICATION

อุปกรณ์แจ้งเหตุเพลิงไหม้

FIRE ALARM EQUIPMENT

“HORING LIH” รุ่น: AH-8022 อุปกรณ์ตรวจจับแก๊ส LPG, NGV, Propane

“HORING LIH” Model: AH-0822 Gas Detector LPG, NGV, Propane

รายละเอียดผลิตภัณฑ์

- รุ่น AH-8822 ใช้เทคโนโลยีขั้นสูง ให้การตรวจจับที่แม่นยำสูง ใช้พลังงานต่ำ และตอบสนองได้รวดเร็ว
- สามารถตรวจจับก๊าซธรรมชาติและก๊าซโพรเพนได้ มีบัสเซอร์และไฟแสดงสถานะ LED ในตัว เพื่อแจ้งเตือนด้วยเสียงและแสง
- เมื่ออยู่ในสถานะเตือนภัย จะมีเสียงดังและไฟกะพริบ
- ไฟ LED สีเขียวติดค้างขณะเฝ้าระวัง และไฟ LED สีแดงกะพริบเมื่ออยู่ในสถานะเตือนภัย
- รองรับแหล่งจ่ายไฟคู่ 12VDC และ 24VDC ภายในเครื่องเดียวกัน โดยไม่ต้องปรับตั้งค่าใด ๆ
- มีอะแดปเตอร์ไฟฟ้าให้เลือกใช้งานแบบ 110VAC หรือ 220VAC
- มีเอาต์พุตรีเลย์ 1 ชุด : COM, NO, NC สำหรับรุ่นมาตรฐาน CE



Specifications				
Model	AH-0822			
Approval	UL		CE	
Power Source	24V DC	12V DC	24V DC	12V DC
Standby Current	25~30mA	40~45mA	35~40mA	65~70mA
Alarm Current	40~70mA	50~75mA	75~90mA	90~105mA
Warm-up Period	5~8 minutes		about 35 seconds	
Sensitivity	0.021 ~ 0.300% (Propane) 0.050 ~ 0.714% (Methane)		0.050 ~ 0.300%	
Alarm Sound	85dB/3M and above		90dB/M and above	
Relay Output			1 set of contact	
Detection Type	Natural Gas & Propane Gas			
Ambient Temperature	-10°C ~ +55°C			
Dimensions	102 mm (Dia.) x 40.5 mm(H)			
Weight	About 130g			

