



TRANE®



ODYSSEY

Split System 5-20 Tons

Light Commercial

TTA/TTH R410A Series 50Hz

Odyssey R410A (Option)

Cool You, Cool The Earth

New design of industrial air conditioner with non-ozone depletion refrigerant R-410A to provide steady comfort with reliability and flexibility for all applications in split air conditioning system together with effort to cool down the earth and protect our environment



Maximum Efficiency

- Lower noise operation and higher efficiency with new generation scroll compressor.
- Single rotating assembly minimizes the friction and mechanical losses.

Quality and Reliability

- Scroll compressors are applied with excellent reliability and high efficiency.
- Unit is run tested prior to leaving the production line.
- Protect compressor damage from unstable electrical source or mis-phase connection with under / over voltage phase protection device.
- Power paint finish for TTH and TTA model.

Ease of Service

- Service shut-off valve
- Single side access on condensor.
- Multiple removable panels on AHU.
- Color and numbered wiring.

TTH Air Handling Unit

- TTH for horizontal air discharge
- Belt drive
- Thermal expansion device
- Fan motor hp output will be specially selected to properly match with Free Blow application

TTA Condensing Unit

- External current overload for compressor
- Under / over voltage and phase protector
- High & low pressure switch
- Refrigerant shut-off valve



Product Specifications

Models	Indoor unit		TTH060JD	TTH075JD	TTH100JD	TTH120JD	TTH160JD	TTH180JD	TTH210JD	TTH240JD
	Outdoor unit		TTKB60KD	TTA075JD	TTA100JD	TTA120JD	2xTTA075JD	2xTTA100JD	2xTTA100JD	2xTTA120JD
Electrical Data	Power Supply	V/ph/Hz	380-415/3/50							
Performance Data	Cooling Capacity	Btu/h	60,000	75,000	100,000	120,000	150,000	180,000	200,000	240,000
	Nominal Airflow	CFM	2,000	2,500	3,400	4,000	5,300	6,000	7,000	8,000
Indoor Units										
No. of Refrigerant Circuit			1	1	1	1	2	2	2	2
Expansion Device	Type		Thermostatic Expansion Valve							
Fan	Type		Forward Curve Centrifugal Fan - Belt Drive							
	Qty		1	1	2	2	2	2	2	2
Fan Motor*	Output	hp	0.75	1	2	2	2	3	3	5
	RLA x Qty	A	1.61	1.99	3.66	3.66	3.66	5.16	5.16	8.80
Filter	Type		1-Inch Thickness Washable Aluminium							
Dimensions	H x W x D	mm	520 x 1,406 x 916		520x1,771x916		620x1,774x916		798 x 2,059 x 1,260	
Weight		kg	87	92	136	141	180	189	214	240
Refrigerant Pipe Size (per each circuit)	Liquid	in	3/8	1/2	1/2	1/2	1/2	1/2	1/2	1/2
	Suction	in	1-1/8	1-1/8	1-1/8	1-3/8	1-1/8	1-1/8	1-1/8	1-3/8
Outdoor Units										
No. of Refrigerant Circuit	per each CDU		1	1	1	1	1	1	1	1
Compressor	Type		Hermetic Scroll							
	RLA x Qty	A	9.8	17.9	17.9	21.4	2 x 17.9	2 x 17.9	2 x 17.9	2 x 21.4
Fan Motor	RLA x Qty	A	0.88 x 2	1.5	1.5	1.5	2 x 1.5	2 x 1.5	2 x 1.5	2 x 1.5
Dimensions (H x W x D)	per each CDU	mm	1,254 x 988 x 350		1,070 x 952 x 1,042		2 x (1,070 x 952 x 1,042)			
Weight	per each CDU	kg	95	164	180	192	2 x 164	2 x 180	2 x 180	2 x 192
Piping Connection Type			Shut-off Valve : Braze Connection							
Refrigerant Pipe Size (per each CDU)	Liquid	in	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2
	Suction	in	7/8	1-1/8	1-1/8	1-3/8	1-1/8	1-1/8	1-1/8	1-3/8
Refrigerant			R-410A							

Note: 1. Capacity is rated at ARI conditions of 80°/67° FDB/FWB for Indoor & 95° FDB for Outdoor
 2. Outdoor unit dimensions depth does not include the dimensions of unit's legs.
 3. Fan motor hp output will be specially selected to properly match with Free Blow application.
 4. Design and specification are subject to change without notice.



Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$12 billion global business committed to a world of sustainable progress and enduring results. For more information, visit www.tranethailand.com

บริษัท บี.เค.แอร์สัพพลาย จำกัด

611,613 ถนนพระราม3 แขวงบางโพงพาง เขตยานนาวา กรุงเทพมหานคร 10120

T: 02-284-2826 02-294-5260 02-294-5261 02-294-2972 F: 02-294-2973

email: bkairsupply@hotmail.com LINE ID: nick_arwin

©2019 Trane All rights reserved

SSA5-SLB003-TTH-R410A-EN February 26, 2019

