

40QBS-W Series

Chiilled Water Cool-Floor Standing 39,000 - 75,000 BTUH



World's Nº.1 Air Conditioning Expert

THE REPORT OF THE PARTY OF THE

www.bkairsupply.com

40QBS-W Series



The latest innovation from the world leader in air conditioning, Carrier, introduces the all-new floor standing split air conditioning system. The 40Q, millennium design, inside and out, will provide you with cool comfort via a variety of control functions.



ELECTRONIC THERMOSTAT Standard supplied with new, user friendly, large LCD display CONTROL PANEL easy to read the temperature from distance or even in the dark.

Special features

- SWING MODE with vertical supply grille ensures coolness throughout the room. Easily to maintenance.
- Washable filter enhances Indoor Air Quality.
- Adjustable Fan Speed with AUTO FAN cools down the room quickly. MICROPROCESSOR enables precise temperature control up to 1 degree Celsius.
- TIME DELAY, installed safety protection system, protects and prolongs usage life of compressor by delaying it for 3 minutes before restarting.
- New slim design and new color make 40QBS blended to your decor of any room. Durable anti-rust casing helps the unit last longer.

Specification <mark>(รายละเอียดของเค</mark> รื	รื่อง)		Chilled Water Coil - Floor Standing Type (ตั้งพื้น)							
Model Name(ชื่อรุ่น)	Indoor		40QBS							
	(เครื่องภายใน)		036W	048W	060W					
Cooling Capacity (ความสามารถในการทำความเย็น)		w	11,694	15,358	22,069					
		Btu/hr.	39,900	52,400	75,300					
Power Consumption (กำลังไฟฟ้า)			316	370						
Power Supply (ระบบไฟฟ้า)		V/Ph/Hz	220/1/50							
Operating Current (กระแสไฟฟ้า)		Amp.	1.48	1.68	1.68					
Indoor Air Circulation, Max. (ปรีมาณลมหมุนเวียน) m³/h		m ³ /h	2,040	2,720	3,400					
c			1,200	1,600	2,000					
Sound Pressure Level (Turbo/Hi/Med/Low) dB(A)			53/47/44/41	55/49/45/42	56/51/46/43					
Dimension - Indoor unit	Height	mm.	1,800							
(ขนาดของเครื่อง)	Wedth	mm.	690	780						
	Depth	mm.	330	330 390						
Net Weight (น้ำหนักเครื่อง)	•	kg.	83.0	98.5	102.0					
Connecting Pipe - Indoor	Water Inlet (FPT)	inch	1/2							
(ขนาดท่อที่ใช้)	Water Outlet (FPT)	inch	1/2							
	Drain O.D. (ท่อน้ำทึ้ง)	inch	3/4							

Note : Cooling Capacity based on 1. Cooling capacity based on Entering water temp. 44 °F /Leaving water temp. 54 °F 2. Water Temperature Rise : 10°F 3. Entering Air Temperature 80°F.db / 67°F.wb 4. High Speed

Preformance Data

Model	Entering Water Temperature (°F)	Entering Air Temperature (°F db / °F wb)															
		76/63			78/65			80/67			82/69						
		тн	SH	GPM	FT.WG	TH	SH	GPM	FT.WG	TH	SH	GPM	FT.WG	TH	SH	GPM	FT.WG
40QBS036W	40	37,000	29,200	7.37	8.03	43,000	31,200	8.57	10.46	49,400	33,200	9.84	13.35	56,000	35,200	11.16	16.67
	45	27,600	24,600	5.51	4.73	32,000	26,300	6.38	6.11	37,500	28,200	7.48	8.08	44,100	30,200	8.80	10.74
	50	20,100	20,100	4.01	2.66	23,000	22,000	4.60	3.38	27,200	23,700	5.43	4.52	31,900	25,400	6.37	5.97
40QBS048W	40	48,600	38,300	9.68	14.45	56,400	40,900	11.24	18.80	64,700	43,500	12.89	23.91	73,300	46,100	14.60	29.81
	45	36,300	32,400	7.25	8.52	42,100	34,600	8.39	11.01	49,300	37,100	9.83	14.55	57,800	39,700	11.54	19.29
	50	26,400	26,400	5.27	4.79	30,300	29,000	6.06	6.11	35,800	31,100	7.15	8.14	41,900	33,300	8.37	10.74
40QBS060W	40	69,900	53,200	13.92	12.04	80,600	56,800	16.06	15.48	92,000	60,400	18.33	19.55	103,900	64,000	20.69	24.22
	45	52,100	45,000	10.40	7.08	61,000	48,100	12.18	9.32	71,100	51,400	14.18	12.19	82,800	55,100	16.52	15.95
	50	37,800	37,300	7.54	3.96	43,900	40,200	8.76	5.14	51,600	43,200	10.31	6.83	61,100	46,300	12.20	9.18

Note : Water Temperature Rise 10F

บริษัท บี.เค.แอร์ชัพพลาย จำกัด B.K. AIRSUPPLY CO.,LTD.

611,613 ถนนพระราม 3 แขวงบางโพงพาง เขตยานนาวา กรุงเทพฯ 10120 611,613 Rama3 Rd. Bangpongpang, Yannava, Bangkok 10120 Tel : 02-284-2826, 02-294-5260, 02-294-5261, 02-294-2972 Fax : 02-294-2973

Carrier reserves the right to make changes in specifications without prior notice. บริษัทฯ ขอสงวนสิทธิ์ที่จะเปลี่ยนแปลงรายละเอียดข้างต้น โดยมิต้องแจ้งให้ทราบล่วงหน้า



YOUR CARRIER MAN :