



Document Solutions



FS-1040

Laser Printer



Kyocera FS-1040 Printer

RELIABILITY AND DURABILITY IN A COMPACT DESIGN, IDEAL FOR SMALL AND MEDIUM-SIZED BUSINESSES

Designed with the small and medium-sized businesses in mind, the compact but powerful Kyocera ECOSYS FS-1040 printer has all the features that make it an essential element in today's office.



Ecological Operation

- ECOSYS Technology drastically reduces consumable waste, contributing to the protection of the environment
- Quiet operation at 28 dB in Ready Mode and 50 dB when printing, with the ability to function at lower levels while printing in Quiet Mode
- Complies with Energy Star® for efficient energy use

Proven Reliability

- Maximum uptime without the need for user intervention thanks to long-life consumables
- Due to the advanced Japanese ECOSYS Technology, long-life consumables prevent the need to change the drum or other components every time the toner is replaced
- Virtually no user intervention required until 100,000 prints

Increased Productivity

- High speed printing up to 21 ppm and only 8.5 seconds or less for the first page out
- Ability to use a wide range of paper types allowing for a large variety of jobs to be completed internally
- Maximum monthly duty cycle of up to 10,000 pages per month

Maximum Profitability

- High toner yield allows printing up to 2,500 pages
- Ability to print several pages on one sheet (N-up) which significantly reduces paper usage and costs
- Long lasting consumables and components that lead to significant savings and a reduced total cost of ownership

User-Friendly Software Tools

- Simplified device management including access to printer features and preferences
- Easy online toner ordering from select suppliers
- Directly link to Kyocera's driver download web page, ensuring immediate access to the latest print drivers

Basic Specifications

Technology and configuration	Kyocera ECOSYS® Black and White Printer
Pages per minute	Letter: 21 ppm, Legal: 13 ppm, A4: 20 ppm
Warm up time (from power on)	14 seconds or less
First print out time	8.5 seconds or less
Resolution	600 X 600 dpi, Fast: 1200 (1800 x 600 dpi)
Memory	32MB
Duplex printing	Manual
Electrical requirements	120 V: 60Hz/5.4 A; 220 V: 50 Hz/2.8A
Dimensions/Weight	358 mm W x 262 mm D x 241 mm H/6.3 kg
Typical energy consumption (TEC)	120 V: 873 W per hour/week; 220 V: 835 W per hour/week
Noise (ISO)	50 dB(A) printing
Maximum monthly duty cycle	10,000 pages per month

Controller Specifications

CPU / MHz	ARM926EJ / 390 MHz
PDL/Emulations	Host based Graphic Device Interface (GDI)
Supported client operating systems	Certified for Microsoft® Windows Vista® 32/64 bit, Windows XP® 32/64 bit, Windows 7® 32/64 bit, Windows Server 2003, Windows Server 2008 32/64 bit, Mac OS X
Connectivity/Interfaces	High-speed USB 2.0
Drivers	GX Driver, Mac Raster Driver
Additional print features	N-up

Paper Supply

Standard paper sources	250 sheet tray
Standard/maximum paper sources	1 / 1
Standard paper drawer size / Weight	Letter, Legal, A4, 70 x 148 (mm) - 215,9 x 356 (mm) / 60 - 220 gsm
Standard/maximum paper capacity	250 / 250
Input materials	Plain, preprinted, bond, recycled, rough, letterhead, color, pre-punched, high quality, labels, vellum, envelope, cardstock, thick paper, custom
Output capacity	150 sheets

Consumables

Black toner	TK-1112: Toner for 2,500 pages* (Starter Toner Yield: 700 pages) *In accordance with ISO 19752
-------------	---



Specifications and design are subject to changes without prior notice. To find out more about the latest in connectivity, please visit www.kyoceradocumentsolutions.com
All trademarks belong to their respective owners.
KYOCERA Document Solutions America, Inc. Headquarters, Inc.
225 Sand Road, Fairfield, NJ 07004 USA.
©2012 KYOCERA Document Solutions America, Inc.

