

FLUERTE K99

Greater Durability and Longer Life

Durable tread compound with reinforced construction stands up to the challenge of heavy loads and extends tread life.

Excellent Wet Grip and Traction

The four wide straight grooves enhance drainage performance and provide exceptional maneuverability and anti-aquaplaning capabilities on wet surfaces.

Extra Powerful Profile

High rigidity and tough. Combination of deep lugs and sipes prevent uneven wear and enhance handling performance.

MEET THE MULTI-PURPOSE NEEDS OF THE MODERN COMMERCIAL VEHICLE

Size	Ply	Loading Index	Load Capacity (kg)	Speed Rating	Standard Rim	Section Width (mm)	Overall Diameter (mm)	Max. Pressure (kPa)
185R14C	8PR	102/100	900/850	S	5 1/2J	188	652	450
195R14C	8PR	106/104	950/900	S	5 1/2J	206	666	450
205/70R15C	8PR	106/104	950/900	S	6J	205	669	450
215/70R15C	8PR	109/107	1030/975	S	6 1/2J	215	683	450
215/65R16C	8PR	109/107	950/900	S	6J	215	685	450
215/70R16C	8PR	108/106	950/900	S	6J	215	707	450
235/65R16C	8PR	121/119	1215/1150	S	6J	235	712	450