



KAIJU-2

Get to The Trail Peacefully

Variable Pitch Tread Pattern - Advanced sound equipment was used to create a pattern that provides a quiet and smooth highway ride.

Off-Road Performance

The lugs on the shoulder are staggered to improve traction in deep sand and loose dirt.

Performances in Every Condition

Angled, lateral voids were engineered to channel away water in wet conditions and provide forward stability in dry conditions.

MEET YOUR EVERYDAY ON AND OFF-ROAD ADVENTURES

Size	Loading Index	Load Capacity (kg)	Speed Rating	Standard Rim	Section Width (mm)	Overall Diameter (mm)	Max. Pressure (kPa)	UTQG
245/70R16	111 XL	1090	T	7J	248	750	350	560 A B
265/70R16	116 XL	1250	T	8J	272	778	350	560 A B
265/75R16	116 XL	1250	T	7 1/2J	267	804	350	560 A B
265/65R17	116 XL	1250	T	8J	272	776	350	560 A B
285/70R17	120 XL	1400	T	8 1/2J	292	838	350	560 A B
265/60R18	114 XL	1180	T	8J	272	775	350	560 A B
275/65R18	116 XL	1250	T	8J	275	815	350	560 A B
265/50R20	111 XL	1090	T	8 1/2J	277	774	350	560 A B
275/55R20	117 XL	1285	T	8 1/2J	284	810	350	560 A B