

PRESA M/T

Durable Large Blocks

Large blocks for rough appearances, provide more contact point with the road surface for better handling while minimizing noise.

Unique Shoulder Tread Layout

Aggressive shoulder to sidewall blocks for better traction.

Wide and functional shoulder layout provides exceptional off-road capability while maintaining great on-road performance.

Ply Reinforced Sidewall & Stone Ejectors

Optimized 3-ply construction ensures excellent steering stability and side-cut resistance.

Protect the grooves from stone drilling while maintaining traction.

GO-ANYWHERE PERFORMANCE WITH AMAZING TRACTION

Size	Ply	Loading Index	Load Capacity (kg)	Speed Rating	Standard Rim	Section Width (mm)	Overall Diameter (mm)	Max. Pressure (kPa)
215/75R15LT	6PR	100/97	800/730	Q	6J	215	703	248
235/75R15LT	6PR	104/101	900/825	Q	6 1/2J	235	733	248
30X9.50R15LT	6PR	104	900	Q	7 1/2J	241	762	241
235/85R16LT	10PR	120/116	1400/1250	Q	6 1/2J	235	812	345
245/75R16LT	10PR	120/116	1400/1250	Q	7J	248	780	345
265/75R16LT	10PR	123/120	1550/1400	Q	7 1/2J	267	810	345
245/75R17	-	112	1120	S	7J	248	800	248
255/75R17LT	6PR	111/108	1090/1000	Q	7J	255	814	345
265/65R17LT	10PR	120/117	1400/1285	Q	8J	265	776	345
265/70R17LT	8PR	118/115	1320/1215	Q	8J	272	810	345
285/65R17	-	116	1250	S	8 1/2J	285	802	248
265/60R18	10PR	110	1060	S	8J	272	775	240
285/60R18	-	116	1250	S	8 1/2J	285	799	248