



ST-51

Quiet and Comfort

Optimized variable pitch combination design reduces noise effectively and brings dynamic driving experience.

Variable 3D pattern groove design provides comfortable and smooth riding moment.

Handling Accurateness

Structural reinforcement of pattern groove bottom improves handling stability. In between tortuous groove and steel design promote excellent traction performance.

Excellent Braking Performance and Durability

High density slots design and special formula shortens braking distance either in dry and wet conditions.

Unique durable tread formula ensures greater tread life, and provides excellent dry and wet braking performance, drives with confidence.

LONGEVITY AND PERFORMANCE ON HIGHWAY

Size	Loading Index	Load Capacity (kg)	Speed Rating	Standard Rim	Section Width (mm)	Overall Diameter (mm)	Max. Pressure (kPa)	UTQG
235/75R15	109 XL	1030	T	6 1/2J	235	733	340	420 A A
215/65R16	98	750	H	6 1/2J	221	686	300	420 A A
215/70R16	100	800	H	6 1/2J	221	708	300	420 A A
245/70R16	111 XL	1090	T	7J	248	750	340	420 A A
265/70R16	112	1120	T	8J	265	777	300	420 A A
215/60R17	96	710	V	6 1/2J	221	690	300	420 A A
225/60R17	99	775	V	6 1/2J	228	702	300	420 A A
225/65R17	102	850	T	6 1/2J	228	724	300	420 A A
265/65R17	112	1120	T	8J	272	776	300	420 A A
265/70R17	115	1215	T	8J	272	804	300	420 A A
235/55R18	104 XL	900	V	7 1/2J	245	715	340	420 A A
235/60R18	107 XL	975	V	7J	240	739	340	420 A A
265/60R18	110	1060	H	8J	272	775	300	420 A A
275/55R20	117 XL	1285	T	8 1/2J	284	810	340	420 A A
275/60R20	115	1215	T	8J	279	838	300	420 A A