



# ST-55

## Superior Dynamic Performance

Dynamic appearance, while providing more excellent drainage and prevent aquaplaning.

Wide pattern blocks with wide pattern grooves, sharp appearance with sporty feelings.

## Driving Safety

Four broad main grooves are engineered to play a significant role in drainage and anti-skid.

Asymmetric pattern with leading edge in handling performance both of wet and dry conditions.

## Predictable Cornering

The specifically formulated tread compound and reinforced internal construction were engineered to emphasize dry road response, traction, handling and high-speed capabilities.

## PURE STREET PERFORMANCE

Size	Loading Index	Load Capacity (kg)	Speed Rating	Standard Rim	Section Width (mm)	Overall Diameter (mm)	Max. Pressure (kPa)	UTQG
265/50R20	111 XL	1090	V	8 1/2J	277	774	340	400 A A
235/30R22	90 XL	600	W	8 1/2J	242	701	340	400 A A
265/35R22	102 XL	850	V	9 1/2J	271	745	340	400 A A
265/40R22	106 XL	950	V	9 1/2J	271	771	340	400 A A
305/40R22	114 XL	1180	V	11J	313	803	340	400 A A
305/45R22	118 XL	1320	V	10J	303	833	340	400 A A
305/35R24	112 XL	1120	V	11J	313	824	340	400 A A