

SC-901

Longer Driving Mileage

Wear-resistance tread formula can effectively improve mileage and service life.
Tread reinforced block reduces rolling resistance for fuel-saving.

Safety on Wet Surface

Wide drainage groove design is adopted to improve drainage performance of wet and slippery environment.
Continuous steamlined transverse pattern grooves evacuate water more effectively.

Confident Handling on Dry Condition

The herringbone grooves cut the water film productively, safety on both wet and dry conditions.
High tenacity cord in framework better strengthens and increases the anti-damage ability.

COST-EFFECTIVE WITH LONG ENDURANCE

Size	Loading Index	Load Capacity (kg)	Speed Rating	Standard Rim	Section Width (mm)	Overall Diameter (mm)	Max. Pressure (kPa)	UTQG
155/65R13	73	365	T	4 1/2J	157	532	300	360 A A
155/70R13	75	387	T	4 1/2J	157	548	300	360 A A
155/80R13	79	437	T	4 1/2J	157	578	300	360 A A
165/65R13	77	412	T	5J	170	544	300	360 A A
165/70R13	79	437	T	5J	170	562	300	360 A A
165/80R13	83	487	T	4 1/2J	165	594	300	360 A A
175/70R13	82	475	T	5J	177	576	300	360 A A
185/70R13	86	530	T	5 1/2J	189	590	300	360 A A
155/65R14	75	387	T	4 1/2J	157	558	300	360 A A
165/55R14	72	335	V	5J	165	538	300	360 A A
165/60R14	75	387	H	5J	170	554	300	360 A A
165/65R14	79	437	T	5J	170	570	300	360 A A
165/70R14	85 XL	515	T	5J	170	588	300	360 A A
175/65R14	86 XL	475	H	5J	177	584	300	360 A A
175/70R14	84	500	T	5J	177	602	300	360 A A
185/55R14	80	450	H	6J	194	560	300	360 A A
185/60R14	82	475	H	5 1/2J	189	578	300	360 A A
185/65R14	86	530	H	5 1/2J	189	596	300	360 A A
185/70R14	88	560	T	5 1/2J	189	616	300	360 A A

Size	Loading Index	Load Capacity (kg)	Speed Rating	Standard Rim	Section Width (mm)	Overall Diameter (mm)	Max. Pressure (kPa)	UTQG
195/60R14	86	530	H	6J	201	590	300	360 A A
195/70R14	91	615	T	6J	201	630	300	360 A A
175/65R15	84	500	H	5J	177	609	300	360 A A
185/55R15	82	475	V	6J	194	585	300	360 A A
185/60R15	88 XL	560	H	5 1/2J	189	603	300	360 A A
185/65R15	88	560	H	5 1/2J	189	621	300	360 A A
195/50R15	82	475	V	6J	201	577	300	360 A A
195/55R15	85	515	V	6J	201	595	300	360 A A
195/60R15	88	560	V	6J	201	615	300	360 A A
195/65R15	91	615	V/H	6J	201	635	300	360 A A
205/60R15	91	615	V	6J	209	627	300	360 A A
205/65R15	94	670	H	6J	209	647	300	360 A A
205/70R15	96	710	T	6J	209	710	300	360 A A
215/65R15	100 XL	800	H	6 1/2J	221	661	340	360 A A
215/70R15	98	750	T	6 1/2J	221	683	300	360 A A
225/60R15	96	710	V	6 1/2J	228	651	300	360 A A
195/50R16	88	560	V	6J	201	602	300	360 A A
195/55R16	87	545	V	6J	201	620	300	360 A A
195/60R16	89	580	V/H	6J	201	640	300	360 A A
205/60R16	92	630	V	6J	209	652	300	360 A A
215/60R16	95	690	T	6 1/2J	221	664	300	360 A A
215/65R16	98	750	T	6 1/2J	221	686	300	360 A A