



异径直接
REDUCER COUPLING
(S×S) ANSI

Nominal	Structural Diameter						Structural Diameter			
SIZE	d1	d2	I1	d3	d4	I2	D1	D2	d	L
3/4"×1/2"	26.87	26.57	25.5	21.54	21.23	22.5	35.0	29.0	16.0	56.5
1"×1/2"	33.65	33.27	29.0	21.54	21.23	22.5	43.0	29.0	16.0	62.4
1"×3/4"	33.65	33.27	29.0	26.87	26.57	26.0	43.0	35.0	22.0	62.4
1-1/4"×1/2"	42.42	42.04	32.0	21.54	21.23	22.5	52.5	29.0	16.0	68.0
1-1/4"×3/4"	42.42	42.04	32.0	26.87	26.57	26.0	52.5	35.0	22.0	68.0
1-1/4"×1"	42.42	42.04	32.0	33.65	33.27	29.0	52.5	43.0	30.0	68.0
1-1/2"×1/2"	48.56	48.11	36.0	21.54	21.23	22.5	59.0	29.0	16.0	74.0
1-1/2"×3/4"	48.56	48.11	36.0	26.87	26.57	26.0	59.0	35.0	22.0	74.0
1-1/2"×1"	48.56	48.11	36.0	33.65	33.27	29.0	59.0	43.0	30.0	74.0
1-1/2"×1-1/4"	48.56	48.11	36.0	42.42	42.04	32.0	59.0	52.5	38.0	74.0
2"×1/2"	60.63	60.17	39.0	21.54	21.23	22.5	72.0	29.0	16.0	76.0
2"×3/4"	60.63	60.17	39.0	26.87	26.57	26.0	72.0	35.0	22.0	76.0
2"×1"	60.63	60.17	39.0	33.65	33.27	29.0	72.0	43.0	30.0	76.0
2"×1-1/4"	60.63	60.17	39.0	42.42	42.04	32.0	72.0	52.5	38.0	82.0
2"×1-1/2"	60.63	60.17	39.0	48.56	48.11	35.5	72.0	59.0	43.0	82.0
2-1/2"×1-1/2"	73.38	72.85	45.0	48.56	48.11	35.5	88.0	59.0	43.0	92.0
2-1/2"×2"	73.38	72.85	45.0	60.63	60.17	38.5	88.0	72.0	54.0	92.0
3"×1-1/2"	89.31	88.70	48.0	48.56	48.11	35.5	105.0	59.0	43.0	102.4
3"×2"	89.31	88.70	48.0	60.63	60.17	38.5	105.0	72.0	54.0	102.0
3"×2-1/2"	89.31	88.70	48.0	73.38	72.85	45.0	105.0	87.6	67.0	102.0
4"×1-1/2"	114.76	114.10	57.6	48.56	48.11	35.5	132.0	59.0	43.0	116.0
4"×2"	114.76	114.10	57.6	60.63	60.17	38.5	132.0	72.0	54.0	105.5
4"×2-1/2"	114.76	114.10	57.6	73.38	72.85	45.0	132.0	87.6	67.0	116.0
4"×3"	114.76	114.10	57.6	89.31	88.70	48.1	132.0	105.0	82.0	115.4
5"×4"	141.81	141.00	76.0	114.76	114.10	57.6	166.5	132.0	106.0	155.0
6"×5"	168.83	168.00	76.0	141.81	141.00	76.0	190.8	166.5	133.0	188.0
8"×6"	219.84	218.70	103.0	168.83	168.00	76.0	245.3	190.8	158.0	218.0
10"×8"	273.81	272.67	128.6	219.84	218.70	103.0	307.0	245.3	200.0	269.8
12"×10"	324.61	323.47	172.0	273.81	272.67	128.6	364.0	307.0	262.5	325.0



补芯 REDUCER BUSHING (S×S) ANSI

Nominal	Outside	Socket Type		Structural Diameter		
SIZE	D	d1	d2	d	I	L
3/4"×1/2"	26.67	21.54	21.23	17.0	24.0	33.0
1"×3/4"	33.40	26.87	26.57	22.5	27.0	36.0
1-1/4"×1"	42.16	33.65	33.27	28.0	30.0	40.0
1-1/2"×1-1/4"	48.28	42.42	42.04	38.0	34.0	45.0
2"×1-1/2"	60.33	48.56	48.11	42.0	37.0	49.0
2-1/2"×2"	73.03	60.63	60.17	54.0	41.0	55.0
3"×2-1/2"	88.90	73.38	72.85	66.0	47.0	60.0
4"×3"	114.30	89.31	88.70	80.0	49.5	68.0
5"×4"	141.30	114.76	114.10	97.1	57.5	85.0
6"×4"	168.28	114.76	114.10	97.1	60.0	92.5
6"×5"	168.28	141.81	141.00	121.0	67.0	92.5
8"×4"	219.08	114.76	114.10	97.1	60.0	120.0
8"×6"	219.08	168.83	168.00	146.0	76.5	120.0
10"×4"	273.05	114.76	114.10	97.1	60.0	148.0
10"×6"	273.05	168.83	168.00	146.0	76.5	148.0
10"×8"	273.05	219.84	218.70	208.0	102.6	148.0
12"×4"	323.85	114.76	114.10	97.1	60.0	169.0
12"×6"	323.85	168.83	168.00	146.0	76.5	169.0
12"×8"	323.85	219.84	218.70	208.0	103.0	169.0
12"×10"	323.85	273.81	272.67	262.5	128.6	169.0