



补芯 REDUCER BUSHING (S×S) DIN

Nominal	Outside Dia	Socket Type		Structural Diameter		
SIZE	D	d1	d2	d	I	L
25*20	25.0	20.3	20.0	16.0	17.0	18.5
32*20	32.0	20.3	20.0	16.0	17.0	22.0
32*25	32.0	25.3	25.0	21.0	19.5	22.0
40*32	40.0	32.3	32.0	28.0	23.0	26.0
50*20	50.0	20.3	20.0	16.0	17.0	31.0
50*25	50.0	25.3	25.0	21.0	19.5	31.0
50*32	50.0	32.3	32.0	28.0	23.0	31.0
50*40	50.0	40.3	40.0	35.0	27.0	31.0
63*32	63.0	32.3	32.0	28.0	23.0	37.5
63*50	63.0	50.4	50.0	45.0	32.0	37.5
75*50	75.0	50.4	50.0	45.0	32.0	43.5
75*63	75.0	63.4	63.0	56.0	38.5	43.5
90*50	90.0	50.4	50.0	45.0	32.0	51.0
90*63	90.0	63.4	63.0	56.0	38.5	51.0
90*75	90.0	75.4	75.0	67.0	44.0	51.0
110*50	110.0	50.4	50.0	45.0	32.0	61.0
110*63	110.0	63.4	63.0	56.0	38.5	61.0
110*90	110.0	90.5	90.0	80.5	52.0	61.0
140*90	140.0	90.5	90.0	80.5	52.0	76.2
140*110	140.0	110.5	110.1	101.5	62.0	76.2
160*90	160.0	90.5	90.0	80.5	52.0	86.0
160*110	160.0	110.5	110.1	102.0	62.0	86.0
160*140	160.0	140.6	140.1	134.0	77.0	86.0
200*160	200.0	160.6	160.1	151.0	86.0	106.5
225*110	225.0	110.5	110.1	102.0	62.0	118.7
225*160	225.0	160.6	160.1	151.0	86.0	118.7
280*160	280.0	160.6	160.1	150.0	86.0	145.0
280*225	280.0	225.8	225.1	216.0	118.5	145.0
315*225	315.0	225.8	225.1	216.0	119.5	162.5
315*280	315.0	281.0	280.1	267.5	146.0	162.5