



N.P.V.EQUIPMENT LTD.,PART.



异径三通 REDUCER TEE (S×S×S)



Nominal	Socket Type						Structural Diameter				
SIZE	d1	d2	I1	d3	d4	I2	D1	D2	d	L	L1
25*20	24.1	23.8	18.0	19.3	19.0	16.0	34.0	28.0	22.0	58.0	29.0
32*20	31.0	30.7	20.0	19.3	19.0	16.0	43.0	28.0	29.0	62.0	33.0
32*25	31.0	30.7	20.0	24.1	23.8	18.0	43.0	34.0	29.0	67.0	34.0
40*20	39.0	38.6	22.0	19.3	19.0	16.0	53.0	28.0	35.0	68.0	35.5
40*25	39.0	38.6	22.0	24.1	23.8	18.0	53.0	34.0	35.0	72.0	37.5
40*32	39.0	38.6	22.0	31.0	30.7	20.0	53.0	43.0	35.0	79.0	39.5
50*20	49.0	48.6	25.0	19.3	19.0	16.0	66.5	28.0	45.0	74.0	40.5
50*25	49.0	48.6	25.0	24.1	23.8	18.0	66.5	34.0	45.0	78.0	42.5
50*32	49.0	48.6	25.0	31.0	30.7	20.0	66.5	43.0	45.0	85.0	44.5
50*40	49.0	48.6	25.0	39.0	38.6	22.0	66.5	53.0	45.0	93.0	46.5
63*20	61.9	61.4	29.0	19.3	19.0	16.0	84.5	28.0	59.0	82.0	47.5
63*25	61.9	61.4	29.0	24.1	23.8	18.0	84.5	34.0	59.0	86.0	49.5
63*32	61.9	61.4	29.0	31.0	30.7	20.0	84.5	43.0	59.0	93.0	51.5
63*40	61.9	61.4	29.0	39.0	38.6	22.0	84.5	53.0	59.0	101.0	53.5
63*50	61.9	61.4	29.0	49.0	48.6	25.0	84.5	66.5	59.0	111.0	56.5
75*32	73.6	72.3	31.5	31.0	30.7	20.0	95.0	43.0	70.0	100.0	58.5
75*40	73.6	72.3	31.5	39.0	38.6	22.0	95.0	53.0	70.0	106.0	60.5
75*50	73.6	72.3	31.5	49.0	48.6	25.0	95.0	66.5	70.0	116.0	63.5
75*63	73.6	72.3	31.5	61.9	61.4	29.0	95.0	84.5	70.0	130.0	67.5
90*40	88.3	86.9	36.0	39.0	38.6	22.0	113.5	53.0	85.0	115.0	68.0
90*50	88.3	86.9	36.0	49.0	48.6	25.0	113.5	66.5	85.0	125.0	71.0
90*63	88.3	86.9	36.0	61.9	61.4	29.0	113.5	84.5	85.0	139.0	75.0
90*75	88.3	86.9	36.0	73.6	72.3	31.5	113.5	95.0	85.0	150.0	77.5
110*50	107.9	106.4	42.0	49.0	48.6	25.0	138.5	66.5	104.0	137.0	81.0
110*63	107.9	106.4	42.0	61.9	61.4	29.0	138.5	84.5	104.0	151.0	85.0
110*75	107.9	106.4	42.0	73.6	72.3	31.5	138.5	95.0	104.0	162.0	87.5
110*90	107.9	106.4	42.0	88.3	86.9	36.0	138.5	113.5	104.0	177.0	92.0



直接 COUPLING (S×S)

Nominal	Socket Type			Structural Diameter		
SIZE	d1	d2	I	D	d	L
20	19.3	19.0	16.0	28.0	17.0	35.0
25	24.1	23.8	18.0	34.0	22.0	39.0
32	31.0	30.7	20.0	43.0	29.0	43.0
40	39.0	38.6	22.0	53.0	35.0	47.0
50	49.0	48.6	25.0	66.5	45.0	53.0
63	61.9	61.4	29.0	84.5	59.0	61.0
75	73.6	72.3	31.5	95.0	70.0	67.0
90	88.3	86.9	36.0	113.5	85.0	77.0
110	108.0	106.4	42.0	138.5	104.0	90.0