



N.P.V.EQUIPMENT LTD.,PART.

执行标准: JIS K6742 JIS K6776
Conform to: JIS K6742 JIS K6776



Nominal SIZE	D (mm)	Tolerance	T (mm)	Tolerance	公称压力 (MPa)
16A	22	±0.2	2.7	+0.6	1.8
20A	26	±0.2	2.7	+0.6	1.8
25A	32	±0.2	3.2	+0.8	1.8
30A	38	±0.2	3.2	+0.8	1.8
40A	48	±0.2	3.7	+0.8	1.8
50A	60	±0.2	4.1	+0.8	1.5
65A	76	±0.3	4.1	+0.8	1.5
75A	89	±0.3	5.5	+0.8	1.5
100A	114	±0.4	6.6	+1.0	1.5
150A	165	±0.5	9.0	+1.4	1.2
200A	216	±0.7	10.3	+1.4	1.2
250A	267	±0.9	12.7	+1.8	1.2
300A	318	±1.0	15.1	+2.2	1.2

4、PPH / PPR管道 PPH/PPR PIPE

执行标准: GB/T 18742.2-2017 DIN 8077:2007-05
Conform to: GB/T 18742.2-2017 DIN 8077:2007-05



Nominal SIZE	D (mm)	Tolerance	Socket Type							
			S5 (1.0MPa)		S4 (1.25MPa)		S3.2 (1.6MPa)		S2.5 (2.0MPa)	
			T (mm)	Tolerance	T (mm)	Tolerance	T (mm)	Tolerance	T (mm)	Tolerance
20	20.0	+0.30	2.00	+0.30	2.30	+0.40	2.80	+0.40	3.40	+0.50
25	25.0	+0.30	2.30	+0.40	2.80	+0.40	3.50	+0.50	4.20	+0.60
32	32.0	+0.30	2.90	+0.40	3.60	+0.50	4.40	+0.60	5.40	+0.70
40	40.0	+0.40	3.70	+0.50	4.50	+0.60	5.50	+0.70	6.70	+0.80
50	50.0	+0.50	4.60	+0.60	5.60	+0.70	6.90	+0.80	8.30	+1.00
63	63.0	+0.60	5.80	+0.70	7.10	+0.90	8.60	+1.00	10.50	+1.20
75	75.0	+0.70	6.80	+0.80	8.40	+1.00	10.30.3	+1.20	12.50	+1.40
90	90.0	+0.90	8.20	+1.00	10.10	+1.20	12.30	+1.40	15.50	+1.60
110	110.0	+1.00	10.00	+1.10	12.30	+1.40	15.10	+1.70	18.30	+2.00
140	140.0	+1.30	12.70	+1.50	15.70	+1.80	19.20	+2.20	23.30	+2.60
160	160.0	+1.50	14.60	+1.70	17.90	+2.00	21.90	+2.40	26.60	+2.90
200	200.0	+1.80	18.20	+2.10	22.40	+2.50	27.40	+3.00	33.20	+3.60
225	225.0	+2.10	20.50	+2.30	25.20	+2.80	30.80	+3.30	37.40	+3.60
250	250.0	+2.30	22.70	+2.50	27.90	+3.00	34.20	+3.60	-	-
280	280.0	+2.50	25.40	+2.80	31.30	+3.30	38.30	+3.60	-	-
315	315.0	+2.50	28.60	+3.10	35.20	+3.60	-	-	-	-