

APPLICATION / DESCRIPTION

NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIME



Specification

MODEL	LED DOWNLIGHT XZKZGS
BODY MATERIAL	ALUMINUM DIE-CASTING
INPUT VOLTAGE	180-260 VAC 50Hz
LED CHIP	CREE
POWER	2W, 6W, 10W, 20W, 30W
EFFICACY	90-95 Lm/W
COLOR RENDERING INDEX	>90
LED COLOR TEMPERATURE	3000K-6500K
THDi	15%
POWER FACTOR	0.95
WORKING TEMPERATURE	0-45dg
LIGHTING SOURCE LIFE	50000Hrs
DRIVER	FOOKES, LIFUD

MODEL	POWER	CCT	CRI	BEAM ANGLE	INPUT VOLTAGE	DAIMENSION (MM)			MATERIAL	LED CHIP	DRIVER	PRICE
						DIAMETER	CUTTING	HEIGHT				
XZKZGS02	2W	3000K-6500K	>90	24°	AC180-260V	54*54	45*45	49	ALUMINUM DIE-CASTING	CREE	FOOKES	฿555
XZKZGS06	6W	3000K-6500K	>90	24°	AC180-260V	131*54	120*45	49	ALUMINUM DIE-CASTING	CREE	FOOKES	฿930
XZKZGS10	10W	3000K-6500K	>90	24°	AC180-260V	207*54	195*45	49	ALUMINUM DIE-CASTING	CREE	LIFUD	฿1,530
XZKZGS20	20W	3000K-6500K	>90	24°	AC180-260V	397*54	388*45	49	ALUMINUM DIE-CASTING	CREE	LIFUD	฿2,490
XZKZGS30	30W	3000K-6500K	>90	24°	AC180-260V	588*54	577*45	49	ALUMINUM DIE-CASTING	CREE	LIFUD	฿4,125



LED Light source



Driver

