

### APPLICATION / DESCRIPTION

NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIME



### Specification

MODEL	LED DOWNLIGHT XZKFGS
BODY MATERIAL	ALUMINUM DIE-CASTING
INPUT VOLTAGE	180-260 VAC 50Hz
LED CHIP	CREE
POWER	8W, 18W, 16W, 36W
EFFICACY	90-95 Lm/W
COLOR RENDERING INDEX	>90
LED COLOR TEMPERATURE	3000K-6500K
THDi	15%
POWER FACTOR	0.95
WORKING TEMPERATURE	0-45dg
LIGHTING SOURCE LIFE	50000Hrs
DRIVER	LIFUD

MODEL	POWER	CCT	CRI	BEAM ANGLE	INPUT LOLTAGE	DAIMENSION (MM)			MATERIAL	LED CHIP	DRIVER	PRICE
						DIAMATER	CUTTING	HEIGHT				
XZKFGS08	8W	3000K-6500K	>90	24°	AC180-260V	92*92	82*82	50	ALUMINUM DIE-CASTING	CREE	LIFUD	฿1,275
XZKFGS18	18W	3000K-6500K	>90	24°	AC180-260V	120*120	120*120	50	ALUMINUM DIE-CASTING	CREE	LIFUD	฿2,400
XZKFGS16	16W	3000K-6500K	>90	24°	AC180-260V	168*91	158*82	50	ALUMINUM DIE-CASTING	CREE	LIFUD	฿2,205
XZKFGS36	36W	3000K-6500K	>90	24°	AC180-260V	246*132	235*120	50	ALUMINUM DIE-CASTING	CREE	LIFUD	฿4,950

LED Light source



Driver

