

LED DOWNLIGHT XZKGJSA 16W, 24W, 50W

APPLICATION / DESCRIPTION

NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIME



Specification

MODEL	LED DOWNLIGHT XZKGJSA
BODY MATERIAL	ALUMINUM DIE-CASTING
INPUT VOLTAGE	180-260 VAC 50Hz
LED CHIP	CREE
POWER	16W, 24W, 50W
EFFICACY	90-95 Lm/W
COLOR RENDERING INDEX	>90
LED COLOR TEMPERATURE	3000K-6500K
THDi	15%
POWER FACTOR	0.95
WORKING TEMPERATURE	0-45dg
LIGHTING SOURCE LIFE	50000Hrs
DRIVER	LIFUD

MODEL	POWER	CCT	CRI	BEAM ANGLE	INPUT LOLTAGE	DAIMENSION (MM)			MATERIAL	LED CHIP	DRIVER	PRICE
						DIAMATER	CUTTING	HEIGHT				
XZKGJSA16	8W*2	3000K-6500K	>90	15°/24°/38°	AC180-260V	183*113	90*160	80	ALUMINUM DIE-CASTING	CREE	LIFUD	฿1,350
XZKGJSA24	12W*2	3000K-6500K	>90	15°/24°/38°	AC180-260V	230*133	210*110	90	ALUMINUM DIE-CASTING	CREE	LIFUD	฿1,875
XZKGJSA50	25W*2	3000K-6500K	>90	15°/24°/38°	AC180-260V	265*155	245*135	110	ALUMINUM DIE-CASTING	CREE	LIFUD	฿3,150



LED Light source



Driver

