

APPLICATION / DESCRIPTION

NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIME



Specification

MODEL	LED DOWNLIGHT XZKXT
BODY MATERIAL	ALUMINUM DIE-CASTING
INPUT VOLTAGE	180-260 VAC 50Hz
LED CHIP	CREE
POWER	7W, 12W, 18W, 25W, 35W
EFFICACY	90-95 Lm/W
COLOR RENDERING INDEX	>90
LED COLOR TEMPERATURE	3000K-6500K
THDi	15%
POWER FACTOR	0.95
WORKING TEMPERATURE	0-45dg
LIGHTING SOURCE LIFE	50000Hrs
DRIVER	LIFUD

MODEL	POWER	CCT	CRI	BEAM ANGLE	INPUT LOLTAGE	DAIMENSION (MM)			MATERIAL	LED CHIP	DRIVER	PRICE
						DIAMATER	CUTTING	HEIGHT				
XZKXT07	7W	3000K-6500K	>90	60°	AC180-260V	87	80	33	ALUMINUM DIE-CASTING	CREE	LIFUD	฿495
XZKXT12	12W	3000K-6500K	>90	60°	AC180-260V	115	105	42	ALUMINUM DIE-CASTING	CREE	LIFUD	฿675
XZKXT18	18W	3000K-6500K	>90	60°	AC180-260V	142	130	50	ALUMINUM DIE-CASTING	CREE	LIFUD	฿975
XZKXT25	25W	3000K-6500K	>90	60°	AC180-260V	169	135	58	ALUMINUM DIE-CASTING	CREE	LIFUD	฿1,275
XZK0T35	35W	3000K-6500K	>90	60°	AC180-260V	217	220	70	ALUMINUM DIE-CASTING	CREE	LIFUD	฿1,605

LED Light source



Driver

