

### APPLICATION / DESCRIPTION

NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIME



### Specification

MODEL	LED DOWNLIGHT XZKSS
BODY MATERIAL	ALUMINUM
INPUT VOLTAGE	180-260 VAC 50Hz
LED CHIP	CREE
POWER	10W
EFFICACY	90-95 Lm/W
COLOR RENDERING INDEX	>90
LED COLOR TEMPERATURE	3000K-6500K
THDi	15%
POWER FACTOR	0.95
WORKING TEMPERATURE	0-45dg
LIGHTING SOURCE LIFE	50000Hrs
DRIVER	LIFUD

MODEL	POWER	CCT	CRI	BEAM ANGLE	INPUT VOLTAGE	DAIMENSION (MM)			MATERIAL	LED CHIP	DRIVER	PRICE
						DIAMETER	CUTTING	HEIGHT				
XZKSS10R	10W	3000K-6500K	>90	15°/24°/38°	AC180-260V	91	92	102	reflector silver, rose golden,	CREE	LIFUD	฿1,080
XZKSS10S	10W	3000K-6500K	>90	15°/24°/38°	AC180-260V	94x75	85*76	102	off white, off black	CREE	LIFUD	฿1,080

LED Light source

CREE

Driver

LIFUD

