

APPLICATION / DESCRIPTION

NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIME



Specification

MODEL	LED DOWNLIGHT XZKTA
BODY MATERIAL	ALUMINUM DIE-CASTING
INPUT VOLTAGE	180-260 VAC 50Hz
LED CHIP	CREE
POWER	10W, 15W, 20W, 25W, 30W
EFFICACY	90-95 Lm/W
COLOR RENDERING INDEX	>90
LED COLOR TEMPERATURE	3000K-6500K
THDi	15%
POWER FACTOR	0.95
WORKING TEMPERATURE	0-45dg
LIGHTING SOURCE LIFE	50000Hrs
DRIVER	FOOKES

MODEL	POWER	CCT	CRI	BEAM ANGLE	INPUT VOLTAGE	DAIMENSION (MM)			MATERIAL	LED CHIP	DRIVER	PRICE
						DIAMETER	CUTTING	HEIGHT				
XZKTA10	10W	3000K-6500K	>90	15°/24°/38°	AC180-260V	50	120	165	ALUMINUM DIE-CASTING	CREE	FOOKES	฿1,305
XZKTA15	15W	3000K-6500K	>90	15°/24°/38°	AC180-260V	50	150	195	ALUMINUM DIE-CASTING	CREE	FOOKES	฿1,530
XZKTA20	20W	3000K-6500K	>90	15°/24°/38°	AC180-260V	60	150	210	ALUMINUM DIE-CASTING	CREE	FOOKES	฿1,950
XZKTA25	25W	3000K-6500K	>90	15°/24°/38°	AC180-260V	70	150	218	ALUMINUM DIE-CASTING	CREE	FOOKES	฿2,145
XZKTA30	30W	3000K-6500K	>90	15°/24°/38°	AC180-260V	80	165	230	ALUMINUM DIE-CASTING	CREE	FOOKES	฿2,400



LED Light source



Driver

