

### APPLICATION / DESCRIPTION

NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIME



### Specification

MODEL	LED DOWNLIGHT XZKTZ
BODY MATERIAL	ALUMINUM DIE-CASTING
INPUT VOLTAGE	180-260 VAC 50Hz
LED CHIP	CREE
POWER	18W, 30W, 40W
EFFICACY	90-95 Lm/W
COLOR RENDERING INDEX	>90
LED COLOR TEMPERATURE	3000K-6500K
THDi	15%
POWER FACTOR	0.95
WORKING TEMPERATURE	0-45dg
LIGHTING SOURCE LIFE	50000Hrs
DRIVER	LIFUD

MODEL	POWER	CCT	CRI	BEAM ANGLE	INPUT VOLTAGE	DAIMENSION (MM)			MATERIAL	LED CHIP	DRIVER	PRICE
						DIAMETER	CUTTING	HEIGHT				
XZKTZ18	18W	3000K-6500K	>90	15°/24°/38°	AC180-260V	66	165	-	ALUMINUM DIE-CASTING	CREE	LIFUD	฿2,145
XZKTZ30	30W	3000K-6500K	>90	15°/24°/38°	AC180-260V	83	195	-	ALUMINUM DIE-CASTING	CREE	LIFUD	฿2,550
XZKTZ40	40	3000K-6500K	>90	15°/24°/38°	AC180-260V	100	210	-	ALUMINUM DIE-CASTING	CREE	LIFUD	฿3,225



LED Light source



Driver

