

LED DOWNLIGHT XZKIS 12W

APPLICATION / DESCRIPTION

NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIME



Specification

| | |
|-----------------------|---------------------|
| MODEL | LED DOWNLIGHT XZKIS |
| BODY MATERIAL | ALUMINUM |
| INPUT VOLTAGE | 180-260 VAC 50Hz |
| LED CHIP | CREE |
| POWER | 12W |
| EFFICACY | 90-95 Lm/W |
| COLOR RENDERING INDEX | >90 |
| LED COLOR TEMPERATURE | 3000K-6500K |
| THDi | 15% |
| POWER FACTOR | 0.95 |
| WORKING TEMPERATURE | 0-45dg |
| LIGHTING SOURCE LIFE | 50000Hrs |
| DRIVER | LIFUD |

| MODEL | POWER | CCT | CRI | BEAM ANGLE | INPUT VOLTAGE | DAIMENSION (MM) | | | MATERIAL | LED CHIP | DRIVER | PRICE |
|---------|-------|-------------|-----|------------|---------------|-----------------|---------|--------|----------|----------|--------|---------|
| | | | | | | DIAMETER | CUTTING | HEIGHT | | | | |
| XZKIS12 | 12W | 3000K-6500K | >90 | 24° | AC180-260V | 85 | 75 | 105 | ALUMINUM | CREE | LIFUD | ฿ 1,020 |

LED Light source



Driver

