



LED FLOOD LIGHT 100W CLEAR

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES

SPECIFICATION

BODY MATERIAL	: ALUMINUM DIE CAST
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
DRIVER	: CE
POWER	: 100W \pm 10%
LUMINOUS FLUX	: 10,000lm
EFFICACY	: 100lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 6500K
VIEW ANGLE	: >100°
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10°C To -50°C
LIGHTING SOURCE LIFE	: 50,000Hrs.
IP PROTECTION RATING	: IP66



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg.	
XZ-FL/100C	100	SMD	50	230	200	-	



LED FLOOD LIGHT 150W CLEAR

APPLICATION/DESCRIPTION

* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

- BODY MATERIAL : ALUMINUM DIE CAST
- INPUT VOLTAGE : 85-305VAC
- LED CHIP : SMD
- DRIVER : CE
- POWER : 150W±10%
- LUMINOUS FLUX : 15,000lm
- EFFICACY : 100lm/W
- COLOR RENDERING INDEX : >70
- LED COLOR TEMPERATURE : 6500K
- VIEW ANGLE : >100°
- POWER FACTOR : >0.95
- WORKING TEMPERATURE : -10°C TO -50°C
- LIGHTING SOURCE LIFE : 50,000Hrs.
- IP PROTECTION RATING : IP66

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
RADIO DISTURBANCE LIMITS
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
RoHS

MODEL	LAMP		DIMENSION (mm.)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg.	
XZ-FL/150C	150	SMD	60	290	260	-	