

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

BODY MATERIAL	: PLASTIC + ALUMINUM & PC COVER
INPUT VOLTAGE	: 85-305 VAC ,50 Hz.
LED CHIP	: SMD
POWER	: 7W
LUMINOUS FLUX	: 630lm
EFFICACY	: 90lm/w
COLOR RENDERING INDEX	: 80
LED COLOR TEMPERATURE	: 6000K
VIEW ANGLE	: 120°
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
 RADIO DISTURBANCE LIMITS
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
 RoHS

MODEL	LAMP		DIMENSION (mm.)		REMARK
	WATT	TYPE	Ø	H	
XZ-R63-7W	7	SMD LED	63	100	



LED BULB 15W R95

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

BODY MATERIAL	: PLASTIC + ALUMINUM & PC COVER
INPUT VOLTAGE	: 85-305 VAC ,50 Hz.
LED CHIP	: SMD
POWER	: 15W
LUMINOUS FLUX	: 1350lm
EFFICACY	: 90lm/w
COLOR RENDERING INDEX	: 80
LED COLOR TEMPERATURE	: 6000K
VIEW ANGLE	: 120°
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
RADIO DISTURBANCE LIMITS
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
RoHS

MODEL	LAMP		DIMENSION (mm.)		REMARK
	WATT	TYPE	Ø	H	
XZ-R95-15W	15	SMD LED	96	129	