



**FLOOD LIGHT 100W Model : XZ-SD-020**

**APPLICATION/DESCRIPTION**

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- \* WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- \* HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



**SPECIFICATION**

MATERIAL	: Aluminum+lens
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 100W
LUMINOUS FLUX	: 13000 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

**STANDARD**

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:  
 RADIO DISTURBANCE LIMITS  
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE  
 RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH Kg	REMARK
	WATT	TYPE	W	L	H		
XZ-SD-020	100	SMD				5.2	



**FLOOD LIGHT 150W Model : XZ-SD-020**

**APPLICATION/DESCRIPTION**

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- \* WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- \* HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



**SPECIFICATION**

MATERIAL	: Aluminum+lens
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 150W
LUMINOUS FLUX	: 19500 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

**STANDARD**

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:  
 RADIO DISTURBANCE LIMITS  
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE  
 RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-SD-020	150	SMD				6.4	



**FLOOD LIGHT 200W Model : XZ-SD-020**

**APPLICATION/DESCRIPTION**

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- \* WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- \* HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



**SPECIFICATION**

MATERIAL	: Aluminum+lens
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 200W
LUMINOUS FLUX	: 26000 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

**STANDARD**

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:  
 RADIO DISTURBANCE LIMITS  
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE  
 RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH Kg	REMARK
	WATT	TYPE	W	L	H		
XZ-SD-020	200	SMD				7.5	