



FLOOD LIGHT ZENON 100W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

MATERIAL	: Aluminum+glass
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 100W
LUMINOUS FLUX	: 11000 lm
EFFICACY	: 110 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-FZN100	100	SMD				2.4	



FLOOD LIGHT ZENON 150W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

MATERIAL	: Aluminum+glass
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 150W
LUMINOUS FLUX	: 16500 lm
EFFICACY	: 110 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-FZN150	150	SMD				3	



FLOOD LIGHT ZENON 200W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

MATERIAL	: Aluminum+glass
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 200W
LUMINOUS FLUX	: 20000 lm
EFFICACY	: 100 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH Kg	REMARK
	WATT	TYPE	W	L	H		
XZ-FZN200	200	SMD				3.8	