



FLOOD LIGHT 200W Model : XZ-FL-CL35

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

MATERIAL	: Aluminum+lens
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 200W
LUMINOUS FLUX	: 26000 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
RADIO DISTURBANCE LIMITS
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-FL-CL35	200	SMD	401	200	232	6.5	



FLOOD LIGHT 300W Model : XZ-FL-CL35

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

MATERIAL	: Aluminum+lens
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 300W
LUMINOUS FLUX	: 39000 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
 RADIO DISTURBANCE LIMITS
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
 RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-FL-CL35	300	SMD	521	260	232	10.5	



FLOOD LIGHT 400W Model : XZ-FL-CL35

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

MATERIAL	: Aluminum+lens
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 400W
LUMINOUS FLUX	: 52000 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
RADIO DISTURBANCE LIMITS
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-FL-CL35	400	SMD	521	260	248	10.5	



FLOOD LIGHT 600W Model : XZ-FL-CL35

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

MATERIAL	: Aluminum+lens
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 600W
LUMINOUS FLUX	: 78000 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
RADIO DISTURBANCE LIMITS
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-FL-CL35	600	SMD	521	521	232	10.5	



FLOOD LIGHT 800W Model : XZ-FL-CL35

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

MATERIAL	: Aluminum+lens
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 800W
LUMINOUS FLUX	: 104000 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
 RADIO DISTURBANCE LIMITS
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
 RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-FL-CL35	800	SMD	521	521	232	12.5	