



**HIGHBAY LINEAR 100W**

**APPLICATION/DESCRIPTION**

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- \* WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- \* HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



**SPECIFICATION**

MATERIAL	: Aluminum + lens
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD Lumileds
POWER	: 100W
LUMINOUS FLUX	: >11000 lm
EFFICACY	: >110 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10°C-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

**STANDARD**

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:  
 RADIO DISTURBANCE LIMITS  
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE  
 RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-HBL-019S3	100	SMD					



**HIGHBAY LINEAR 150W**

**APPLICATION/DESCRIPTION**

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- \* WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- \* HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



**SPECIFICATION**

MATERIAL	: Aluminum + lens
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 150W
LUMINOUS FLUX	: >16500 lm
EFFICACY	: >110 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K±500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10°C-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

**STANDARD**

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:  
 RADIO DISTURBANCE LIMITS  
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE  
 RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-HBL-019S3	150	SMD					



**HIGHBAY LINEAR 200W**

**APPLICATION/DESCRIPTION**

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- \* WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- \* HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



**SPECIFICATION**

MATERIAL	: Aluminum + lens
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD Lumileds
POWER	: 200W
LUMINOUS FLUX	: >22000 lm
EFFICACY	: >110 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10°C-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

**STANDARD**

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:  
 RADIO DISTURBANCE LIMITS  
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE  
 RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-HBL-019S3	200	SMD					