

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE 3000K-6500K
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR FACTORY WHAREHOUSE STORE ETC.

SPECIFICATION

| | |
|-----------------------|----------------------|
| BODY MATERIAL | : ALUMINUM & PC/LENS |
| INPUT VOLTAGE | : 85-305 VAC ,50 Hz. |
| LED CHIP | : LUMILEDS |
| DRIVER | : MEANWELL |
| POWER | : 100W |
| LUMINOUS FLUX | : 13000lm |
| EFFICACY | : 130lm/w |
| COLOR RENDERING INDEX | : 80 |
| LED COLOR TEMPERATURE | : 5700K |
| VIEW ANGLE | : 60°,90°,120° |
| THDi | : <15% |
| POWER FACTOR | : >0.95 |
| WORKING TEMPERATURE | : -10-50°C |
| LIGHTING SOURCE LIFE | : >50,000Hrs |
| IP PROTECTION RATING | : IP65 |



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

| MODEL | LAMP | | DIMENSION (mm.) | | | WEIGH | REMARK |
|---------------|------|---------|-----------------|-----|----|-------|--------|
| | WATT | TYPE | W | L | H | Kg. | |
| XZ-UFO-100W-Q | 100 | SMD LED | 278 | 278 | 60 | 3.2 | |

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE 3000K-6500K
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR FACTORY WHAREHOUSE STORE ETC.

SPECIFICATION

| | |
|-----------------------|----------------------|
| BODY MATERIAL | : ALUMINUM & PC/LENS |
| INPUT VOLTAGE | : 85-305 VAC ,50 Hz. |
| LED CHIP | : LUMILEDS |
| DRIVER | : MEANWELL |
| POWER | : 150W |
| LUMINOUS FLUX | : 19500lm |
| EFFICACY | : 130lm/w |
| COLOR RENDERING INDEX | : 80 |
| LED COLOR TEMPERATURE | : 5700K |
| VIEW ANGLE | : 60°,90°,120° |
| THDi | : <15% |
| POWER FACTOR | : >0.95 |
| WORKING TEMPERATURE | : -10-50°C |
| LIGHTING SOURCE LIFE | : >50,000Hrs |
| IP PROTECTION RATING | : IP65 |



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

| MODEL | LAMP | | DIMENSION (mm.) | | | WEIGH | REMARK |
|---------------|------|---------|-----------------|-----|----|-------|--------|
| | WATT | TYPE | W | L | H | Kg. | |
| XZ-UFO-150W-Q | 150 | SMD LED | 328 | 328 | 70 | 4.3 | |

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE 3000K-6500K
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR FACTORY WHAREHOUSE STORE ETC.

SPECIFICATION

| | |
|-----------------------|----------------------|
| BODY MATERIAL | : ALUMINUM & PC/LENS |
| INPUT VOLTAGE | : 85-305 VAC ,50 Hz. |
| LED CHIP | : LUMILEDS |
| DRIVER | : MEANWELL |
| POWER | : 200W |
| LUMINOUS FLUX | : 26000lm |
| EFFICACY | : 130lm/w |
| COLOR RENDERING INDEX | : 80 |
| LED COLOR TEMPERATURE | : 5700K |
| VIEW ANGLE | : 60°,90°,120° |
| THDi | : <15% |
| POWER FACTOR | : >0.95 |
| WORKING TEMPERATURE | : -10-50°C |
| LIGHTING SOURCE LIFE | : >50,000Hrs |
| IP PROTECTION RATING | : IP65 |



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

| MODEL | LAMP | | DIMENSION (mm.) | | | WEIGH | REMARK |
|---------------|------|---------|-----------------|-----|----|-------|--------|
| | WATT | TYPE | W | L | H | Kg. | |
| XZ-UFO-200W-Q | 200 | SMD LED | 388 | 388 | 75 | 5.5 | |