



LED Highbay 100W UFO-SUN

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

BODY MATERIAL	: ALUMINUM DIE CAST
INPUT VOLTAGE	: 85-305 VAC ,50 Hz.
LED CHIP	: LUMILEDS / OSRAM / SANAI
DRIVER	: CE / MEANWELL / MOSO / INVENTRONIC
POWER	: 100W
LUMINOUS FLUX	: 14000lm
EFFICACY	: 140lm/w
COLOR RENDERING INDEX	: 70
LED COLOR TEMPERATURE	: 6500K
VIEW ANGLE	: 60°,90°,120°
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs
IP PROTECTION RATING	: IP65



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
 RADIO DISTURBANCE LIMITS
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
 RoHS

MODEL	LAMP		DIMENSION (mm.)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg.	
XZ-HBS100	100	SMD LED	260	260	135	4.2	

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

BODY MATERIAL	: ALUMINUM DIE CAST
INPUT VOLTAGE	: 85-305 VAC ,50 Hz.
LED CHIP	: LUMILEDS / OSRAM / SANAN
DRIVER	: CE / MEANWELL / MOSO / INVENTRONICS
POWER	: 150W
LUMINOUS FLUX	: 21000lm
EFFICACY	: 140lm/w
COLOR RENDERING INDEX	: 70
LED COLOR TEMPERATURE	: 6500K
VIEW ANGLE	: 60°,90°,120°
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs
IP PROTECTION RATING	: IP65



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg.	
XZ-HBS150	150	SMD LED	260	260	135	4.2	

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

BODY MATERIAL	: ALUMINUM DIE CAST
INPUT VOLTAGE	: 85-305 VAC ,50 Hz.
LED CHIP	: LUMILED
DRIVER	: CE / MEANWELL / MOSO / INVENTRONICS
POWER	: 200W
LUMINOUS FLUX	: 28000lm
EFFICACY	: 140lm/w
COLOR RENDERING INDEX	: 70
LED COLOR TEMPERATURE	: 6500K
VIEW ANGLE	: 60°,90°,120°
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs
IP PROTECTION RATING	: IP65



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg.	
XZ-HBS200	200	SMD LED	290	290	157	5.8	