

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE 3000K-6500K
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR FACTORY WHAREHOUSE STORE ETC.



SPECIFICATION

BODY MATERIAL	: ALUMINUM DIA CAST
INPUT VOLTAGE	: 85-305 VAC ,50 Hz.
LED CHIP	: SMD
DRIVER	: IC
POWER	: 100W
LUMINOUS FLUX	: 9500lm
EFFICACY	: 95lm/w
COLOR RENDERING INDEX	: 70
LED COLOR TEMPERATURE	: 6500K
VIEW ANGLE	: 60°
THDi	: <15%
POWER FACTOR	: >0.9
WORKING TEMPERATURE	: -10~50°C
LIGHTING SOURCE LIFE	: >50,000Hrs
IP PROTECTION RATING	: IP44

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
 RADIO DISTURBANCE LIMITS
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
 RoHS

MODEL	LAMP		DIMENSION (mm.)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg.	
XZ-UFO-100W	100	SMD LED	348	348	126	-	

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE 3000K-6500K
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR FACTORY WHAREHOUSE STORE ETC.



SPECIFICATION

BODY MATERIAL	: ALUMINUM DIA CAST
INPUT VOLTAGE	: 85-305 VAC ,50 Hz.
LED CHIP	: SMD
DRIVER	: IC
POWER	: 150W
LUMINOUS FLUX	: 14250lm
EFFICACY	: 95lm/w
COLOR RENDERING INDEX	: 70
LED COLOR TEMPERATURE	: 6500K
VIEW ANGLE	: 60°
THDi	: <15%
POWER FACTOR	: >0.9
WORKING TEMPERATURE	: -10~50°C
LIGHTING SOURCE LIFE	: >50,000Hrs
IP PROTECTION RATING	: IP44

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
 RADIO DISTURBANCE LIMITS
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
 RoHS

MODEL	LAMP		DIMENSION (mm.)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg.	
XZ-UFO-150W	150	SMD LED	348	348	126	-	

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE 3000K-6500K
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR FACTORY WHAREHOUSE STORE ETC.



SPECIFICATION

BODY MATERIAL	: ALUMINUM DIA CAST
INPUT VOLTAGE	: 85-305 VAC ,50 Hz.
LED CHIP	: SMD
DRIVER	: IC
POWER	: 200W
LUMINOUS FLUX	: 19000lm
EFFICACY	: 95lm/w
COLOR RENDERING INDEX	: 70
LED COLOR TEMPERATURE	: 6500K
VIEW ANGLE	: 60°
THDi	: <15%
POWER FACTOR	: >0.9
WORKING TEMPERATURE	: -10~50°C
LIGHTING SOURCE LIFE	: >50,000Hrs
IP PROTECTION RATING	: IP44

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
 RADIO DISTURBANCE LIMITS
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
 RoHS

MODEL	LAMP		DIMENSION (mm.)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg.	
XZ-UFO-200W	200	SMD LED	348	348	126	-	