

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE 3000K-6500K
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR FACTORY WHAREHOUSE STORE ETC.



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 85-305 VAC ,50 Hz.
LED CHIP	: -
DRIVER	: -
POWER	: 100W
LUMINOUS FLUX	: 8000lm
EFFICACY	: 80lm/w
COLOR RENDERING INDEX	: 80
LED COLOR TEMPERATURE	: 6500K
VIEW ANGLE	: 60°,90°
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs
IP PROTECTION RATING	: IP65



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
 RADIO DISTURBANCE LIMITS
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
 RoHS

MODEL	LAMP		DIMENSION (mm.)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg.	
XZ-UFOA-100W	100	SMD LED	280	280	137	4.2	

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE 3000K-6500K
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR FACTORY WHAREHOUSE STORE ETC.



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 85-305 VAC ,50 Hz.
LED CHIP	: -
DRIVER	: -
POWER	: 150W
LUMINOUS FLUX	: 12000lm
EFFICACY	: 80lm/w
COLOR RENDERING INDEX	: 80
LED COLOR TEMPERATURE	: 6500K
VIEW ANGLE	: 60°,90°
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs
IP PROTECTION RATING	: IP65



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg.	
XZ-UFOA-150W	150	SMD LED	342	342	152	4.2	

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE 3000K-6500K
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR FACTORY WHAREHOUSE STORE ETC.



SPECIFICATION

BODY MATERIAL	: ALUMINUM
INPUT VOLTAGE	: 85-305 VAC ,50 Hz.
LED CHIP	: -
DRIVER	: -
POWER	: 200W
LUMINOUS FLUX	: 16000lm
EFFICACY	: 80lm/w
COLOR RENDERING INDEX	: 80
LED COLOR TEMPERATURE	: 6500K
VIEW ANGLE	: 60°,90°
THDi	: <15%
POWER FACTOR	: >0.9
WORKING TEMPERATURE	: -10~50°C
LIGHTING SOURCE LIFE	: >50,000Hrs
IP PROTECTION RATING	: IP65



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
 RADIO DISTURBANCE LIMITS
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
 RoHS

MODEL	LAMP		DIMENSION (mm.)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg.	
XZ-UFOA-200W	200	SMD LED	400	400	156	5.8	