



LED Highbay Linear 20W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM + PC Cover
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 20W
LUMINOUS FLUX	: 1800lm
EFFICACY	: 90lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700K-7000k
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10° - 50°C
LIGHTING SOURCE LIFE	: 30,000 hrs.
COVER	: MILKY
FINISH COLOR	: WHITE , BLACK , SILVER

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-XT0312A	20	SMD	1200	100	65	



LED Highbay Linear 36W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM + PC Cover
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 36W
LUMINOUS FLUX	: 3000lm
EFFICACY	: >85lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700K-7000k
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10° - 50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.
COVER	: MILKY
FINISH COLOR	: WHITE , BLACK , SILVER

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-XT0412A	36	SMD	1200	150	65	



LED Highbay Linear 40W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM + PC Cover
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 40W
LUMINOUS FLUX	: 3600lm
EFFICACY	: 90lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700K-7000k
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10° - 50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.
COVER	: MILKY
FINISH COLOR	: WHITE , BLACK , SILVER

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-XT0512A	40	SMD	1200	200	65	



LED Highbay Linear 50W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM + PC Cover
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 50W
LUMINOUS FLUX	: 4500lm
EFFICACY	: 90lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700K-7000k
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10° - 50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.
COVER	: MILKY
FINISH COLOR	: WHITE , BLACK , SILVER

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-XT0612A	50	SMD	1200	250	65	



LED Highbay Linear 60W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM + PC Cover
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 60W
LUMINOUS FLUX	: 5400lm
EFFICACY	: 90lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700K-7000k
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10° - 50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.
COVER	: MILKY
FINISH COLOR	: WHITE , BLACK , SILVER

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-XT0712A	60	SMD	1200	300	65	