



LED BATTEN / LINEAR LIGHT 10W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM + PC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: EPISTAR
POWER	: 10W
LUMINOUS FLUX	: 800-900lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 6500K
BEAM ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10° - 50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS



MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-XT3680-10W	10	SMD	80	300	36	



LED BATTEN / LINEAR LIGHT 20W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM + PC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: EPISTAR
POWER	: 20W
LUMINOUS FLUX	: 1700-1800lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 6500K
BEAM ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10° - 50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

- TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
- RADIO DISTURBANCE LIMITS
- ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
- RoHS



MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-XT3680-20W	20	SMD	80	600	36	



LED BATTEN / LINEAR LIGHT 30W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM + PC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: EPISTAR
POWER	: 30W
LUMINOUS FLUX	: 2600-2800lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 6500K
BEAM ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10° - 50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

- TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
- RADIO DISTURBANCE LIMITS
- ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
- RoHS



MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-XT3680-30W	30	SMD	80	900	36	



LED BATTEN / LINEAR LIGHT 40W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM + PC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: EPISTAR
POWER	: 40W
LUMINOUS FLUX	: 3600-3800lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 6500K
BEAM ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10° - 50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS



MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-XT3680-40W	40	SMD	80	1200	36	



LED BATTEN / LINEAR LIGHT 50W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



SPECIFICATION

BODY MATERIAL	: ALUMINUM + PC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: EPISTAR
POWER	: 50W
LUMINOUS FLUX	: 4600-4800lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 6500K
BEAM ANGLE	: 120°
THDi	: 15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10° - 50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS



MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-XT3680-50W	50	SMD	80	1500	36	