



## LED LINEAR LIGHT 18W

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

BODY MATERIAL	: ALUMINUM + PC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 18W
LUMINOUS FLUX	: 1600lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 6500K
THDi	: 15%
POWER FACTOR	: >0.6
WORKING TEMPERATURE	: -10° - 50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-T8-600-JHD02	18	SMD	25	600	75	



## LED LINEAR LIGHT 28W

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

BODY MATERIAL	: ALUMINUM + PC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 28W
LUMINOUS FLUX	: 2400lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 6500K
THDi	: 15%
POWER FACTOR	: >0.6
WORKING TEMPERATURE	: -10° - 50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-T8-900-JHD02	28	SMD	25	900	75	



## LED LINEAR LIGHT 36W

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

BODY MATERIAL	: ALUMINUM + PC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 36W
LUMINOUS FLUX	: 3200lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 6500K
THDi	: 15%
POWER FACTOR	: >0.6
WORKING TEMPERATURE	: -10° - 50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-T8-1200-JHD02	36	SMD	25	1200	75	



## LED LINEAR LIGHT 48W

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

BODY MATERIAL	: ALUMINUM + PC
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 48W
LUMINOUS FLUX	: 4000lm
EFFICACY	: >80lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 6500K
THDi	: 15%
POWER FACTOR	: >0.6
WORKING TEMPERATURE	: -10° - 50°C
LIGHTING SOURCE LIFE	: 50,000 hrs.

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			REMARK
	WATT	TYPE	W	L	H	
XZ-T8-1500-JHD02	48	SMD	25	1500	75	