



STREET LIGHT GEN2-3P 150W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

MATERIAL	: Aluminum + lens
INPUT VOLTAGE	: 200-240 VAC
LED CHIP	: SMD
POWER	: 150W
LUMINOUS FLUX	: 21000 lm
EFFICACY	: 140 lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
 RADIO DISTURBANCE LIMITS
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
 RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-STU150	150	SMD				11	



STREET LIGHT GEN2-3P 200W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

MATERIAL	: Aluminum + lens
INPUT VOLTAGE	: 200-240 VAC
LED CHIP	: SMD
POWER	: 200W
LUMINOUS FLUX	: 28000 lm
EFFICACY	: 140 lm/W
COLOR RENDERING INDEX	: >80
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
 RADIO DISTURBANCE LIMITS
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
 RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-STU200	200	SMD				12	