



STREET LIGHT 200W Modelal : XZ-LD-052S

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

MATERIAL	: Aluminum + lens
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 200W
LUMINOUS FLUX	: 36000 lm
EFFICACY	: 180 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
RADIO DISTURBANCE LIMITS
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-LD-052S	150	SMD				8.5	



STREET LIGHT 300W Modelal : XZ-LD-052S

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

MATERIAL	: Aluminum + lens
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 300W
LUMINOUS FLUX	: 54000 lm
EFFICACY	: 180 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
RADIO DISTURBANCE LIMITS
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-LD-052S	300	SMD				11.8	