



**LED STREET LIGHT 100W**

**APPLICATION/DESCRIPTION**

\* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



**SPECIFICATION**

- MATERIAL : Aluminum + lens
- INPUT VOLTAGE : 85-305 VAC
- LED CHIP : SMD
- POWER : 100W
- LUMINOUS FLUX : 11000 lm
- EFFICACY : 110 lm/W
- COLOR RENDERING INDEX : >70
- LED COLOR TEMPERATURE : 2700K-6000K
- THDi : <15%
- POWER FACTOR : >0.9
- WORKING TEMPERATURE : -10°C - 50°C
- LIGHTING SOURCE LIFE : >50,000 Hrs.

**STANDARD**

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:  
 RADIO DISTURBANCE LIMITS  
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE  
 RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-LD-051S	100	SMD	510	510	180	9.5	



## LED STREET LIGHT 150W

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES



### SPECIFICATION

MATERIAL	: Aluminum + lens
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 150W
LUMINOUS FLUX	: 16500 lm
EFFICACY	: 110 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700K-6000K
THDi	: <15%
POWER FACTOR	: >0.9
WORKING TEMPERATURE	: -10°C - 50°C
LIGHTING SOURCE LIFE	: >50,000 Hrs.

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-LD-051S	150	SMD	510	510	180	9.5	