



T8 8W ALU PC 1000 LUMEN

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

| | |
|-----------------------|---------------------------------|
| TUBE MATERIAL | : Aluminum+PC Cover |
| INPUT VOLTAGE | : 180-260 VAC ,50 Hz. |
| LED CHIP | : SMD EVERLIGHT/SAMSUNG/LUMILED |
| POWER | : 8W |
| LUMINOUS FLUX | : 1000 lm |
| EFFICACY | : 130 lm/W |
| COLOR RENDERING INDEX | : 80 |
| LED COLOR TEMPERATURE | : 6500K \pm 500K |
| BEAM ANGLE | : >130°-190° |
| THDi | : <15% |
| POWER FACTOR | : > 0.95 |
| WORKING TEMPERATURE | : -10-50°C |
| LIGHTING SOURCE LIFE | : >50,000Hrs |
| DIFFUSER | : MILKY |
| LAMP TERMINAL | : G13 |



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

| MODEL | LAMP | | DIMENSION (mm.) | | | WEIGH | REMARK |
|------------|------|---------|-----------------|---|---|-------|--------|
| | WATT | TYPE | W | L | H | g | |
| XZ-T8MA008 | 8 | SMD LED | | | | | |



T8 9W ALU PC 1200 LUMEN

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

| | |
|-----------------------|---------------------------------|
| TUBE MATERIAL | : Aluminum+PC Cover |
| INPUT VOLTAGE | : 180-260 VAC ,50 Hz. |
| LED CHIP | : SMD EVERLIGHT/SAMSUNG/LUMILED |
| POWER | : 9W |
| LUMINOUS FLUX | : 1200 lm |
| EFFICACY | : 130 lm/W |
| COLOR RENDERING INDEX | : 80 |
| LED COLOR TEMPERATURE | : 6500K \pm 500K |
| BEAM ANGLE | : >130°-190° |
| THDi | : <15% |
| POWER FACTOR | : > 0.95 |
| WORKING TEMPERATURE | : -10-50°C |
| LIGHTING SOURCE LIFE | : >50,000Hrs |
| DIFFUSER | : MILKY |
| LAMP TERMINAL | : G13 |



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

| MODEL | LAMP | | DIMENSION (mm.) | | | WEIGH | REMARK |
|------------|------|---------|-----------------|---|---|-------|--------|
| | WATT | TYPE | W | L | H | g | |
| XZ-T8MA009 | 9 | SMD LED | | | | | |



T8 14W ALU PC 2100 LUMEN


APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

| | |
|-----------------------|---------------------------------|
| TUBE MATERIAL | : Aluminum+PC Cover |
| INPUT VOLTAGE | : 180-260 VAC ,50 Hz. |
| LED CHIP | : SMD EVERLIGHT/SAMSUNG/LUMILED |
| POWER | : 14W |
| LUMINOUS FLUX | : 2100 lm |
| EFFICACY | : 150 lm/W |
| COLOR RENDERING INDEX | : 80 |
| LED COLOR TEMPERATURE | : 6500K \pm 500K |
| BEAM ANGLE | : >130°-190° |
| THDi | : <15% |
| POWER FACTOR | : > 0.95 |
| WORKING TEMPERATURE | : -10-50°C |
| LIGHTING SOURCE LIFE | : >50,000Hrs |
| DIFFUSER | : MILKY |
| LAMP TERMINAL | : G13 |



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
 RADIO DISTURBANCE LIMITS
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
 RoHS

| MODEL | LAMP | | DIMENSION (mm.) | | | WEIGH | REMARK |
|------------|------|---------|-----------------|------|----|-------|--------|
| | WATT | TYPE | W | L | H | g | |
| XZ-T8MA014 | 14 | SMD LED | 27 | 1198 | 29 | 280 | |



T8 18W ALU PC 2400 LUMEN


APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

| | |
|-----------------------|---------------------------------|
| TUBE MATERIAL | : Aluminum+PC Cover |
| INPUT VOLTAGE | : 180-260 VAC ,50 Hz. |
| LED CHIP | : SMD EVERLIGHT/SAMSUNG/LUMILED |
| POWER | : 18W |
| LUMINOUS FLUX | : 2400 lm |
| EFFICACY | : 130 lm/W |
| COLOR RENDERING INDEX | : 80 |
| LED COLOR TEMPERATURE | : 6500K ± 500K |
| BEAM ANGLE | : >130°-190° |
| THDi | : <15% |
| POWER FACTOR | : > 0.95 |
| WORKING TEMPERATURE | : -10-50°C |
| LIGHTING SOURCE LIFE | : >50,000Hrs |
| DIFFUSER | : MILKY |
| LAMP TERMINAL | : G13 |



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
 RADIO DISTURBANCE LIMITS
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
 RoHS

| MODEL | LAMP | | DIMENSION (mm.) | | | WEIGH | REMARK |
|------------|------|---------|-----------------|------|----|-------|--------|
| | WATT | TYPE | W | L | H | g | |
| XZ-T8MA018 | 18 | SMD LED | 27 | 1198 | 29 | 280 | |



T8 25W ALU PC 3200 LUMEN


APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

| | |
|-----------------------|---------------------------------|
| TUBE MATERIAL | : Aluminum+PC Cover |
| INPUT VOLTAGE | : 180-260 VAC ,50 Hz. |
| LED CHIP | : SMD EVERLIGHT/SAMSUNG/LUMILED |
| POWER | : 25W |
| LUMINOUS FLUX | : 3200 lm |
| EFFICACY | : 130 lm/W |
| COLOR RENDERING INDEX | : 80 |
| LED COLOR TEMPERATURE | : 6500K ± 500K |
| BEAM ANGLE | : >130°-190° |
| THDi | : <15% |
| POWER FACTOR | : > 0.95 |
| WORKING TEMPERATURE | : -10-50°C |
| LIGHTING SOURCE LIFE | : >50,000Hrs |
| DIFFUSER | : MILKY |
| LAMP TERMINAL | : G13 |



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
 RADIO DISTURBANCE LIMITS
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
 RoHS

| MODEL | LAMP | | DIMENSION (mm.) | | | WEIGH | REMARK |
|------------|------|---------|-----------------|------|----|-------|--------|
| | WATT | TYPE | W | L | H | g | |
| XZ-T8MA025 | 25 | SMD LED | 27 | 1198 | 29 | 280 | |