

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE 2700K-6500K
- * HAVE WHITE OR NARURAL WARM WHITE TO INSTALL ON FACTORY BUILDING TOWER WEREHOUSE ETC,



SPECIFICATION

TUBE MATERIAL	: Aluminum Inside
INPUT VOLTAGE	: 180-260 VAC ,50 Hz.
LED CHIP	: SMD EVERLIGHT/SAMSUNG/LUMILEDS
POWER	: 9W
LUMINOUS FLUX	: 1000 lm
EFFICACY	: 110 lm/W
COLOR RENDERING INDEX	: 80
LED COLOR TEMPERATURE	: 6500K ± 500K
BEAM ANGLE	: >150 °
THDi	: <15%
POWER FACTOR	: > 0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs
DIFFUSER	: MILKY
LAMP TERMINAL	: G13



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
 RADIO DISTURBANCE LIMITS
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARAN
 RoHS

MODEL	LAMP		DIMENSION (mm.)			WEIGH	REMARK
	WATT	TYPE	W	L	H	g	
XZ-T8PC09	9	SMD LED					

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE 2700K-6500K
- * HAVE WHITE OR NARURAL WARM WHITE TO INSTALL ON FACTORY BUILDING TOWER WEREHOUSE ETC,



SPECIFICATION

TUBE MATERIAL	: Aluminum Inside
INPUT VOLTAGE	: 180-260 VAC ,50 Hz.
LED CHIP	: SMD EVERLIGHT/SAMSUNG/LUMILEDS
POWER	: 16W
LUMINOUS FLUX	: 2100 lm
EFFICACY	: 115 lm/W
COLOR RENDERING INDEX	: 80
LED COLOR TEMPERATURE	: 6500K ± 500K
BEAM ANGLE	: >150 °
THDi	: <15%
POWER FACTOR	: > 0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs
DIFFUSER	: MILKY
LAMP TERMINAL	: G13



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARAN

RoHS

MODEL	LAMP		DIMENSION (mm.)			WEIGH	REMARK
	WATT	TYPE	W	L	H	g	
XZ-T8PC016	16	SMD LED	27	1198	27	250	

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

TUBE MATERIAL	: Aluminum Inside
INPUT VOLTAGE	: 180-260 VAC ,50 Hz.
LED CHIP	: SMD EVERLIGHT/SAMSUNG/LUMILEDS
POWER	: 18W
LUMINOUS FLUX	: 2100 lm
EFFICACY	: 115 lm/W
COLOR RENDERING INDEX	: 80
LED COLOR TEMPERATURE	: 6500K ± 500K
BEAM ANGLE	: >150 °
THDi	: <15%
POWER FACTOR	: > 0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs
DIFFUSER	: MILKY
LAMP TERMINAL	: G13



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARAN

RoHS

MODEL	LAMP		DIMENSION (mm.)			WEIGH	REMARK
	WATT	TYPE	W	L	H	g	
XZ-T8PC018	18	SMD LED	27	1198	27	250	