



## LED BULB 2W FILAMENT

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- \* WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- \* HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

### SPECIFICATION

BODY MATERIAL	: PLASTIC + ALUMINUM
INPUT VOLTAGE	: 180-260 VAC ,50 Hz.
LED CHIP	: EPISTAR
POWER	: 2W
LUMINOUS FLUX	: 200lm
EFFICACY	: 100lm/w
COLOR RENDERING INDEX	: 80
LED COLOR TEMPERATURE	: 6500K
VIEW ANGLE	: 360°
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50° C
LIGHTING SOURCE LIFE	: >50,000Hrs



### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:  
RADIO DISTURBANCE LIMITS  
ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE  
RoHS

MODEL	LAMP		DIMENSION (mm.)		WEIGH	REMARK
	WATT	TYPE	Ø	H	Kg.	
XZ-C2-2W	2	SMD LED	35	98	0.038	

### APPLICATION/DESCRIPTION

- \* NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- \* WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- \* HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



### SPECIFICATION

BODY MATERIAL	: PLASTIC + ALUMINUM
INPUT VOLTAGE	: 180-260 VAC ,50 Hz.
LED CHIP	: EPISTAR
POWER	: 6W
LUMINOUS FLUX	: 600lm
EFFICACY	: 100lm/w
COLOR RENDERING INDEX	: 80
LED COLOR TEMPERATURE	: 6500K
VIEW ANGLE	: 360°
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

### STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:  
 RADIO DISTURBANCE LIMITS  
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE  
 RoHS

MODEL	LAMP		DIMENSION (mm.)		WEIGH	REMARK
	WATT	TYPE	Ø	H	Kg.	
XZ-C2-6W	6	SMD LED	35	120	0.038	